



链滴

druid connection holder is null错误记录

作者: [714593351](#)

原文链接: <https://ld246.com/article/1445476605487>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

<p>最近系统增加了几个功能后，会频繁出现</p>

```
<pre class="brush: java">java.sql.SQLException: connection holder is null
  com.alibaba.druid.pool.DruidPooledConnection.checkState(DruidPooledConnection.java:103)
  com.alibaba.druid.pool.DruidPooledConnection.prepareStatement(DruidPooledConnection.java:306)
  org.apache.jsp.list_jsp._jspService(list_jsp.java:121)
  org.apache.jasper.runtime.HttpJspBase.service(HttpJspBase.java:70)
  javax.servlet.http.HttpServlet.service(HttpServlet.java:717) </pre>
```

<p>错误</p>

<p> </p>

<p>百度搜索了下，发现是由于druid配置有问题，之前把removeAbandonedTimeout从1800s改为80s，觉得3分钟足够了，导致当有些SQL慢的时候回报上述错误。 </p>

<p>查看DRUID监控界面： </p>

<table class="table table-bordered">

<tbody>

<tr>

<td class="td_lable" valign="top">连接持有时间分布</td>

<td>0,53,31,8,3,140,34,0</td>

<td class="lang">连接持有时间分布，分布区间为[0-1 ms, 1-10 ms, 10-100 ms, 100ms-1s, 1-10 s, 10-100 s, 100-1000 s, >1000 s]</td>

</tr>

</tbody>

</table>

<p>发现100-1000s的连接很多。 </p>

<p> </p>

<p>参考1： < target="_blank" title="druid连接池的问题connection holder is null" href="http://www.oschina.net/question/115287_132883">druid连接池的问题connection holder is null </p>

<p>参考2： Druid连接池一个设置引发的血案 </p>