

Struts2 项目中自定义返回结果类型

作者: [terry](#)

原文链接: <https://ld246.com/article/1445691516755>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

```

<pre class="prettyprint">先实现一个类去继承StrutsResultSupport, baseAction继承了ActionSupport
public class SysResultAction extends StrutsResultSupport{
    @Override
    protected void doExecute(String finalLocation, ActionInvocation invocation) throws Exception {
        HttpServletRequest request = ServletActionContext.getRequest();
        HttpServletResponse response = ServletActionContext.getResponse();
        System.out.println("finalLocation="+finalLocation);
        System.out.println("(BaseAction)invocation.getAction()="+((baseAction)invocation.getAction());
        System.out.println("进入了 SysResultAction ...");
        //eg redirect
        String baseUrl = request.getContextPath() + finalLocation.replace("WEB-INF/", "");
        String RedirectUrl = baseUrl.substring(0,baseUrl.lastIndexOf("/")+1);
        response.sendRedirect( RedirectUrl + "test_TAction.do" );
    }
}

```

在修改struts2核心配置配置文件

<!-- 配置全局结果及异常映射 配置文件包-->

```

<package name="base-default" extends="struts-default" >
    <!-- 自定义结果集类型 -->
    <result-types>
        <result-type name="myRedirectResult" class="cn.terry.commons.exception.SysResultAction"></result-type>
    </result-types>
    <!-- 全局结果集 -->
    <global-results>
        <result name="MRR" type="myRedirectResult">/WEB-INF/test/test.jsp</result>
        <result name="sysError">/WEB-INF/jsp/error.jsp</result>
        <result name="input">/WEB-INF/jsp/error.jsp</result>
    </global-results>
    <!-- 全局错误结果集 -->
    <global-exception-mappings>
        <exception-mapping result="sysError" exception="cn.terry.commons.exception.SysException"></exception-mapping>
        <exception-mapping result="input" exception="java.lang.Exception"></exception-mapping>
    </global-exception-mappings>
</package>

```

在添加action

```

public class userAction extends baseAction {
    // 自定义返回结果类型定义,会输出定义的内容
    public String defineResult() throws Exception {
        return "MRR";
    }
}

```

访问 项目名称 (/斜线不能少) 加 nsfw/user/user_defineResult.do 就会跳转到测试页面</pre>