

# Struts2 配置自定义结果集

作者: [terry](#)

原文链接: <https://ld246.com/article/1445697138221>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

```

<div>
  <span style="font-size:12px;">先实现一个类去继承StrutsResultSupport, baseAction继承了ActionSupport</span>
</div>
<div>
  <span style="font-size:12px;">public class SysResultAction extends StrutsResultSupport{</span>
</div>
<div>
  <span style="font-size:12px;"><span> </span>@Override</span>
</div>
<div>
  <span style="font-size:12px;"><span> </span>protected void doExecute(String finalLocation, ActionInvocation invocation) throws Exception {</span>
</div>
<div>
  <span style="font-size:12px;"><span> </span>HttpServletRequest request = ServletActionContext.getRequest();</span>
</div>
<div>
  <span style="font-size:12px;"><span> </span>HttpServletResponse response = ServletActionContext.getResponse();</span>
</div>
<div>
  <span style="font-size:12px;"><span> </span>System.out.println("finalLocation="+finalLocation);</span>
</div>
<div>
  <span style="font-size:12px;"><span> </span>System.out.println("(BaseAction)invocation.getAction()="+ (baseAction)invocation.getAction());</span>
</div>
<div>
  <span style="font-size:12px;"><span> </span>System.out.println("进入了 SysResultAction..");</span>
</div>
<div>
  <span style="font-size:12px;"><span> </span>//eg redirect</span>
</div>
<div>
  <span style="font-size:12px;"><span> </span>String baseURI = request.getContextPath() &nbsp;+ &nbsp;finalLocation.replace("WEB-INF/", "");</span>
</div>
<div>
  <span style="font-size:12px;"><span> </span>String RedirectUrl &nbsp;= baseURI.substring(0,baseURI.lastIndexOf("/")+1);</span>
</div>
<div>
  <span style="font-size:12px;"><span> </span>response.sendRedirect( RedirectUrl + "testTAction.do" );</span>
</div>
<div>
  <span style="font-size:12px;"><span> </span>}</span>
</div>
<div>

```

```

    <span style="font-size:12px;">}</span>
</div>
<div>
    <span style="font-size:12px;"> <br />
</span>
</div>
<div>
    <span style="font-size:12px;">在修改struts2核心配置配置文件</span>
</div>
<div>
    <span style="font-size:12px;">&lt;!-- 配置全局结果及异常映射 配置文件包--&gt;</span>
</div>
<div>
    <span style="font-size:12px;"> <span> </span>&lt;package name="base-default" extends
"struts-default" &gt;</span>
</div>
<div>
    <span style="font-size:12px;"> <span> </span>&lt;!-- 自定义结果集类型 &nbsp;--&gt;</sp
n>
</div>
<div>
    <span style="font-size:12px;"> <span> </span>&lt;result-types&gt;</span>
</div>
<div>
    <span style="font-size:12px;"> <span> </span>&lt;result-type name="myRedirectResult" c
lass="cn.terry.common.exception.SysResultAction"&gt;&lt;/result-type&gt;</span>
</div>
<div>
    <span style="font-size:12px;"> <span> </span>&lt;/result-types&gt;<span> </span></sp
n>
</div>
<div>
    <span style="font-size:12px;"> <span> </span>&lt;!-- 全局结果集 --&gt;</span>
</div>
<div>
    <span style="font-size:12px;"> <span> </span>&lt;global-results&gt;</span>
</div>
<div>
    <span style="font-size:12px;"> <span> </span>&lt;result name="MRR" type="myRedirect
result"&gt;/WEB-INF/test/test.jsp&lt;/result&gt;</span>
</div>
<div>
    <span style="font-size:12px;"> <span> </span>&lt;result name="sysError"&gt;/WEB-INF/j
sp/error.jsp&lt;/result&gt;</span>
</div>
<div>
    <span style="font-size:12px;"> <span> </span>&lt;result name="input"&gt;/WEB-INF/jsp/
error.jsp&lt;/result&gt;</span>
</div>
<div>
    <span style="font-size:12px;"> <span> </span>&lt;/global-results&gt;</span>
</div>
<div>
    <span style="font-size:12px;"> <span> </span>&lt;!-- 全局错误结果集 --&gt;</span>

```

```

</div>
<div>
  <span style="font-size:12px;"> <span> </span>&lt;global-exception-mappings&gt;</spa
>
</div>
<div>
  <span style="font-size:12px;"> <span> </span>&lt;exception-mapping result="sysError" e
ception="cn.terry.commons.exception.SysException"&gt;&lt;/exception-mapping&gt;</span>

</div>
<div>
  <span style="font-size:12px;"> <span> </span>&lt;exception-mapping result="input" exc
ption="java.lang.Exception"&gt;&lt;/exception-mapping&gt;&nbsp;</span>
</div>
<div>
  <span style="font-size:12px;"> <span> </span>&lt;/global-exception-mappings&gt;</spa
>
</div>
<div>
  <span style="font-size:12px;"> <span> </span>&lt;/package&gt;</span>
</div>
<div>
  <span style="font-size:12px;"> <br />
</span>
</div>
<div>
  <span style="font-size:12px;">在添加action</span>
</div>
<div>
  <span style="font-size:12px;">public class userAction extends baseAction {</span>
</div>
<div>
  <span style="font-size:12px;"> <span> </span> // 自定义返回结果类型定义,会输出定义的内
</span>
</div>
<div>
  <span style="font-size:12px;"> <span> </span>public String defineResult() throws Excepti
n {</span>
</div>
<div>
  <span style="font-size:12px;"> <span> </span>return "MRR";</span>
</div>
<div>
  <span style="font-size:12px;"> <span> </span>}</span>
</div>
<div>
  <span style="font-size:12px;">}</span>
</div>
<div>
  <span style="font-size:12px;"> <br />
</span>
</div>
<div>
  <span style="font-size:12px;">访问 项目名称 (/斜线不能少) 加 nsfw/user/user_defineResult

```

```
do 就会跳转到测试页面</span>
</div>
<p>
  <br />
</p>
```