



链滴

struts2 自定义结果集类型

作者: [terry](#)

原文链接: <https://ld246.com/article/1445740957242>

来源网站: 链滴

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

<p>先实现一个类去继承StrutsResultSupport, baseAction继承了ActionSupport</p>
<pre class="prettyprint">public class SysResultAction extends StrutsResultSupport{
 @Override
 protected void doExecute(String finalLocation, ActionInvocation invocation) throws Exceptio
 {
 HttpServletRequest request = ServletActionContext.getRequest();
 HttpServletResponse response = ServletActionContext.getResponse();
 System.out.println("finalLocation=" +finalLocation);
 System.out.println("(BaseAction)invocation.getAction()=" +(baseAction)invocation.getAction
));
 System.out.println("进入了 SysResultAction ...");
 //eg redirect
 String baseUrl = request.getContextPath() + finalLocation.replace("WEB-INF/", "");
 String RedirectUrl = baseUrl.substring(0,baseUrl.lastIndexOf("/")+1);
 response.sendRedirect(RedirectUrl + "test_TAction.do");
 }
}</pre>

<p>在修改struts2核心配置配置文件</p>

```
<!-- 配置全局结果及异常映射 配置文件包-->
<package name="base-default" extends="struts-default" >
    <!-- 自定义结果集类型 -->
    <result-types>
        <result-type name="myRedirectResult" class="cn.terry.commons.exception.SysResultAct
on"></result-type>
    </result-types>
    <!-- 全局结果集 -->
    <global-results>
        <result name="MRR" type="myRedirectResult">/WEB-INF/test/test.jsp</result>
        <result name="sysError">/WEB-INF/jsp/error.jsp</result>
        <result name="input">/WEB-INF/jsp/error.jsp</result>
    </global-results>
    <!-- 全局错误结果集 -->
    <global-exception-mappings>
        <exception-mapping result="sysError" exception="cn.terry.commons.exception.SysExcep
ion"></exception-mapping>
        <exception-mapping result="input" exception="java.lang.Exception"></exception
mapping>
    </global-exception-mappings>
</package></pre>
```

<p>在添加action</p>

```


```

<p>访问 项目名称 (/斜线不能少) 加 nsfw/user/user_defineResult.do 就会跳转到测试页面</p>