



链滴

Spring集成hibernate配置service层事务的 疑问

作者: [Angonger](#)

原文链接: <https://ld246.com/article/1470637538080>

来源网站: 链滴

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

```

<bean id="transactionManager"
  class="org.springframework.orm.hibernate3.HibernateTransactionManager">
  <property name="sessionFactory">
    <ref local="sessionFactory" />
  </property>
</bean>

<bean name="transactionAttributes"
  class="org.springframework.transaction.interceptor.NameMatchTransactionAttributeSource">
  <property name="properties">
    <props>
      <prop key="init*">PROPAGATION_REQUIRED</prop>
      <prop key="save*">PROPAGATION_REQUIRED</prop>
      <prop key="add*">PROPAGATION_REQUIRED</prop>
      <prop key="submit*">PROPAGATION_REQUIRED</prop>
      <prop key="update*">PROPAGATION_REQUIRED</prop>
      <prop key="audit*">PROPAGATION_REQUIRED</prop>
      <prop key="report*">PROPAGATION_REQUIRED</prop>
      <prop key="del*">PROPAGATION_REQUIRED</prop>
      <prop key="find*">PROPAGATION_REQUIRED,readOnly</prop>
      <prop key="load*">PROPAGATION_REQUIRED,readOnly</prop>
      <prop key="edit*">PROPAGATION_REQUIRED,readOnly</prop>
      <prop key="*">PROPAGATION_REQUIRED</prop>
    </props>
  </property>
</bean>

<bean id="nameMatchTxInterceptor"
  class="org.springframework.transaction.interceptor.TransactionInterceptor">
  <property name="transactionManager">
    <ref bean="transactionManager" />
  </property>
  <property name="transactionAttributeSource">
    <ref bean="transactionAttributes" />
  </property>
</bean>

<bean id="autoTxProxyCreator"
  class="org.springframework.aop.framework.autoproxy.BeanNameAutoProxyCreator">
  <property name="interceptorNames">
    <list>
      <idref local="nameMatchTxInterceptor" />
    </list>
  </property>
  <property name="beanNames">
    <list>
      <value>*Service</value>
    </list>
  </property>
</bean>

```

如上的配置，以Service结尾的类全部应用此配置，那么问题来了：连接是在什么时候获取呢？（执行

ervice方法之前? 方法开始?)