



链滴

树莓派3刷centos7连接wifi

作者: [Img1369](#)

原文链接: <https://ld246.com/article/1470756330508>

来源网站: 链滴

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

<p>1、激活wlan0</p>

<p>下载/root/README中的2个文件，重启系统

2、配置/etc/sysconfig/wpa_supplicant文件
如下：</p>

```
<pre class="brush: java; light: true"># Use the flag "-i" before each of your interfaces, like so:
INTERFACES="-ieth1 -iwlan0" ##放开注释
#INTERFACES="" ##注释
```

Use the flag "-D" before each driver, like so:

```
DRIVERS="-Dwext" ##放开注释
```

```
#DRIVERS="" ##注释
```

Other arguments</pre>

<p>

3、配置/etc/sysconfig/network-scripts/wlan0
如下：</p>

```
<pre class="brush: java; light: true">TYPE="Wireless"
BOOTPROTO="dhcp"
NM_CONTROLLED="yes"
DEFROUTE="yes"
NAME="wlan0"
ONBOOT="yes"
WPA="yes"
HWADDR="XX:XX:XX:XX:XX:XX" #此为无线网卡MAC地址，可通过ifconfig获取</pre>
```

<p>

4、配置/etc/wpa_supplicant/wpa_supplicant.conf</p>

<p>如下：</p>

```
<pre class="brush: java; light: true">ctrl_interface=/var/run/wpa_supplicant
ctrl_interface_group=wheel
network={
```

```
    ssid="ssid" #wifi名字
    scan_ssid=1
    psk="password" #wifi密码
    key_mgmt=WPA-PSK #加密方式
```

```
</pre>
```

<p>
5、重启下wlan0
ifup wlan0</p>

<p>6、分配动态ip</p>

```
<p>dhclient wlan0</pre>
```

<p> </p>

<p>参照树莓派吧吧友的，地址：http://tieba.baidu.com/p/4534085576?pid=9248018013&cid=0#89248018013</p>

<p>感谢吧友</p>