



链滴

zabbix 监控服务端和客户端安装配置

作者: [lingfei0312](#)

原文链接: <https://ld246.com/article/1473325854644>

来源网站: 链滴

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)


```
<p style="padding-left: 30px;">步骤3 编译安装zabbix</p>
<p style="padding-left: 60px;">tar &ndash;zxf zabbix-2.4.7.tar.gz</p>
<p style="padding-left: 60px;">cd zabbix-2.4.7</p>
<p style="padding-left: 60px;">./configure &ndash;prefix=/usr/local/zabbix &ndash;enable-
gent</p>
<p style="padding-left: 60px;">make</p>
<p style="padding-left: 60px;">make install</p>
<p style="padding-left: 30px;">步骤4 执行如下命令, 配置zabbix_agentd</p>
<p style="padding-left: 60px;">mkdir /var/log/zabbix</p>
<p style="padding-left: 60px;">chown zabbix.zabbix /var/log/zabbix</p>
<p style="padding-left: 60px;">cp /usr/local/src/zabbix-2.4.7/misc/init.d/fedora/core/zabbix_
gentd /etc/init.d/</p>
<p style="padding-left: 60px;">ln -s /usr/local/zabbix/etc /etc/zabbix</p>
<p style="padding-left: 60px;">ln -s /usr/local/zabbix/sbin/* /usr/sbin/</p>
<p style="padding-left: 60px;">ln -s /usr/local/zabbix/bin/* /usr/bin/</p>
<p style="padding-left: 60px;">sed -i -e 's|LogFile=/tmp|LogFile=/var/log/zabbix|' /etc/zabbi
/zabbix_agentd.conf</p>
<p style="padding-left: 60px;">sed -i -e 's|Server=127.0.0.1|Server=192.168.0.19|' /etc/zabbix
zabbix_agentd.conf</p>
<p style="padding-left: 60px;">sed -i -e 's|ServerActive=127.0.0.1|ServerActive=192.168.0.19:
0051|' /etc/zabbix/zabbix_agentd.conf</p>
<p style="padding-left: 60px;">sed -i -e 's|# Include=/usr/local/etc/zabbix_agentd.conf.d|Inc
ude=/usr/local/zabbix/etc/zabbix_agentd.conf.d|' /etc/zabbix/zabbix_agentd.conf</p>
<p style="padding-left: 60px;">sed -i -e 's|# UnsafeUserParameters=0|UnsafeUserParameter
=1|' /etc/zabbix/zabbix_agentd.conf</p>
<p style="padding-left: 60px;">sed -i -e 's|BASEDIR=/usr/local|BASEDIR=/usr/local/zabbix|' /
tc/init.d/zabbix_agentd</p>
<p style="padding-left: 60px;">chkconfig zabbix_agentd on</p>
```