



链滴

mybatis map foreach 遍历

作者: [justdoit](#)

原文链接: <https://ld246.com/article/1476266272653>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

<p>mybatis 遍历map实例</p>

<p>map 数据如下 Map<String,List<Long>>.</p>

<p> </p>

<p>测试代码如下: </p>

<div class="cnblogs_code">

```
<pre> <span>public</span> <span>void</span> <span>getByMap(){
    Map<String,List<Long>> params= <span>new</span> HashMap<
tring, List<Long>>(<span>);
    List<Long> orgList= <span>new</span> ArrayList<Long>(<span>);
    orgList.add(<span>10000003840076L</span>);
    orgList.add(<span>10000003840080L</span>);
```

```
List<Long> roleList= <span>new</span> ArrayList<Long>(<span>);
```

```
roleList.add(<span>10000000050086L</span>);
```

```
roleList.add(<span>10000012180016L</span>);
```

```
params.put(<span>"org"</span>, orgList);
```

```
params.put(<span>"role"</span>, roleList);
```

```
List<BpmDefUser> list= <span>bpmDefUserDao.getByMap(params);
```

```
System.out.println(list.size());
```

```
</span> </pre>
```

</div>

<p> </p>

<p>dao代码如下: </p>

<div class="cnblogs_code">

```
<pre> <span>public</span> List<BpmDefUser> getByMap(Map<String,List<Long
>> map){
    Map<String,Object> params= <span>new</span> HashMap<String, Ob
ect>(<span>);
    params.put(<span>"relationMap"</span>, map);
    <span>return</span> <span>this</span>.getBySqlKey("getByMap" <span>, p
rams);
```

```
</span> </pre>
```

</div>

<p>xml代码如下: </p>

<div class="cnblogs_code">

```
<pre> <span>&lt;</span> <span>select </span> <span>id</span> <span>=</span>"getByMap" </s
an> <span> resultMap</span> <span>=</span>"BpmDefUser" </span> <span>&gt;</span>
```

```
    <span>&lt;</span> <span>foreach </span> <span>collection</span> <span>=</span>"relatio
Map" </span> <span> index</span> <span>=</span>"key" </span> <span> item</span> <span>=</span>
nt" </span> <span> separator</span> <span>=</span>"union" </span> <span>&gt;</span> <span>
```

```
    SELECT *
    FROM BPM_DEF_USER
```

```
    where RIGHT_TYPE=#{key}
    and OWNER_ID in
    </span><span>&lt;/span><span>foreach </span><span>collection</span><spa
>="ent"</span><span> item</span><span>="id"</span><span> separator</span><spa
>=","</span><span> open</span><span>="("</span><span> close</span><span>=")"</
pan><span>&gt;</span><span>
    #{id}
    </span><span>&lt;/span><span>foreach</span><span>&gt;</span>
<span>&lt;/span><span>foreach</span><span>&gt;</span>

<span>&lt;/span><span>select</span><span>&gt;</span></pre>

</div>
<p><span>index 作为map 的key。 item为map的值，这里使用了嵌套循环，嵌套循环使用ent。 </
pan></p>
```