



链滴

Jhipster 踩过的坑

作者: [xsx](#)

原文链接: <https://ld246.com/article/1482735425519>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

1)

Description:

Field userRepository in com.ejtone.ejt1.security.UserDetailsService required a bean of type 'com.ejtone.ejt1.repository.UserRepository' that could not be found.

Action:

Consider defining a bean of type 'com.ejtone.ejt1.repository.UserRepository' in your configuration.

因为修改的包名，并未全部修改掉

2)

无法加载主类

方法: mvn -N io.takari:maven:wrapper

3)

Spring Security和JWT

登录操作是有两次请求完成，在把Token传给前端后需要前端带着这个Token来认证权限

@PostMapping("/users/quicklogin")

@Timed

```
public ResponseEntity<?> authorizeByQuick(@Valid @RequestBody PhoneVM phoneVM,
HttpServletResponse response) {
```

```
    if(codisService.compareCode(phoneVM.getPhone(),phoneVM.getCode())){
```

```
        User user=userRepository.findOneByPhone(phoneVM.getPhone()).get();
        List<GrantedAuthority> grantedAuths = new ArrayList<GrantedAuthority>();
        grantedAuths.add(new SimpleGrantedAuthority("ROLE_USER"));
```

```
        UsernamePasswordAuthenticationToken authenticationToken =
            new UsernamePasswordAuthenticationToken(user.getLogin(), null,grantedAuths);
        authenticationToken.setDetails(user);
```

```
// Authentication authentication = this.authenticationManager.authenticate(authenticationToken);
```

```
        SecurityContextHolder.getContext().setAuthentication(authenticationToken);
        boolean rememberMe = (phoneVM.isRememberMe() == null) ? false : phoneVM.isRememberMe();
```

```
        String jwt = tokenProvider.createToken(authenticationToken, rememberMe);
        response.addHeader(JWTConfigurer.AUTHORIZATION_HEADER, "Bearer " + jwt);
        return ResponseEntity.ok(new JWTToken(jwt));
```

```
    }else {
```

```
        return new ResponseEntity<Object>("code not true",HttpStatus.BAD_REQUEST);
```

```
    }
```

```
}
```