

nginx+tomcat 配置文件

作者: [lingfei0312](#)

原文链接: <https://ld246.com/article/1484626532027>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

```
<p>nginx.conf</p>
<pre class="brush: java">user nginx;
pid /var/run/nginx.pid;
```

```
worker_processes 8;
worker_rlimit_nofile 102400;
events {
    use epoll;
    worker_connections 102400;
}
http {
```

```
passenger_root /usr/local/rvm/gems/ruby-1.9.3-p51/gems/passenger-5.0.20;
```

```
passenger_ruby /usr/local/rvm/gems/ruby-1.9.3-p51/bin/ruby;
```

```
include mime.types;
charset utf-8;
default_type application/octet-stream;
```

```
log_format main '$remote_addr - $remote_user [$time_local] "$request" '
    '"$status" $body_bytes_sent "$http_referer" '
    '"$http_user_agent" "$http_x_forwarded_for" '
    '"$gzip_ratio" $request_time $bytes_sent $request_length';
```

```
log format srcache_log 'remote_addr - remote_user  
[time_local] "request
```

```
""status" body_bytes_sent request_time bytes_sent  
$request_length
```

```
""[upstream response time] [srcache_fetch_status] [  
rcache_store_status] [srcache_expire];
```

```
set_real_ip_from 10.0.0.0/8;
real_ip_header X-Forwarded-For;
```

```
add_header Access-Control-Allow-Origin *;
add_header Access-Control-Allow-Headers X-Requested-With;
add_header Access-Control-Allow-Methods GET,POST,OPTIONS;
```

```
include /etc/nginx/gzip.conf;
include /etc/nginx/proxy.conf;
```

```

server_names_hash_max_size 512;
server_names_hash_bucket_size 128;
sendfile on;
fastcgi_intercept_errors on;
keepalive_timeout 650;
include /etc/nginx/vhosts/*.conf;
include /etc/nginx/vhosts/stock/*.conf;
include /etc/nginx/vhosts/cyw/*.conf;
include /etc/nginx/vhosts/baye8/*.conf;
include /etc/nginx/vhosts/60/*.conf;

server {
    listen 80;
    server_name localhost;
    root /usr/share/nginx/html;

    location / {
        index index.html index.htm index.php;
    }

    error_page 500 502 503 504 /50x.html;
    location = /50x.html {
        root html;
    }

    location ~ /\.php {
        fastcgi_pass 127.0.0.1:9000;
        fastcgi_index index.php;
        fastcgi_param SCRIPT_FILENAME $document_root$fastcgi_script_name;
        include fastcgi_params;
    }
    location ~ /\.ht {
        deny all;
    }
}

```

include /etc/nginx/vhosts/*.conf;

```

}
```

```

</pre>
```

```

<p>proxy.conf</p>
<pre class="brush: java">#!nginx (-)
# proxy.conf
fastcgi_buffers 32 8k;
proxy_redirect off;
proxy_set_header Host $host;
proxy_set_header X-Real-IP $remote_addr;
proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
client_max_body_size 1024m;
client_body_buffer_size 128k;
proxy_connect_timeout 600;
proxy_send_timeout 600;

```

```
proxy_read_timeout 600;
send_timeout 600;
proxy_buffer_size 16k;
proxy_buffers 4 64k;
proxy_busy_buffers_size 128k;
proxy_temp_file_write_size 128k;
proxy_temp_path /tmp/nginx/temp;
proxy_cache_path /tmp/nginx/cache levels=1:2 keys_zone=cache_zone:2048M inactive=1d m
x_size=20g;
proxy_headers_hash_max_size 512000;
proxy_headers_hash_bucket_size 64000;</pre>
<p>gzip.conf</p>
<pre class="brush: java">gzip on;
# gzip_http_version 1.1;
gzip_disable "MSIE [1-6]\.";
#gzip_disable "Mozilla/4";
gzip_static on;
gzip_comp_level 4;
gzip_proxied any;
gzip_vary on;
gzip_buffers 4 16k;
gzip_min_length 1100;
gzip_types text/plain text/xml text/css application/xml application/xhtml+xml application/rss
xml application/atom_xml application/javascript application/x-javascript;</pre>
<p>vhosts.conf</p>
<pre class="brush: java">upstream mall-cms.messandbox.com {
    server 127.0.0.1:7791;
}
```

```
upstream mall-info.messandbox.com {
server 127.0.0.1:7791;
}
```

```
upstream mall-my.messandbox.com {
server 127.0.0.1:7791;
}
```

```
upstream mall-search.messandbox.com {
server 127.0.0.1:7791;
}
```

```
upstream mall-pay.messandbox.com {
server 127.0.0.1:7791;
}
```

```
upstream mall-sc.messandbox.com {
server 127.0.0.1:7791;
}
```

```
upstream mall-open.messandbox.com {  
server 127.0.0.1:7791;  
}
```

```
upstream mall-common.messandbox.com {  
server 127.0.0.1:7791;  
}
```

```
upstream mall-cs.messandbox.com {  
server 127.0.0.1:7791;  
}
```

```
upstream mall-c.messandbox.com {  
server 127.0.0.1:7791;  
}
```

```
#server {
```

```
listen 80;
```

```
server_name www.ecec.com;
```

```
#access_log /data/logs/b2c2c/access.log main;
```

```
location / {
```

```
root /data/zte/www/html/ecec;
```

```
index index/index.html index/index.htm;
```

```
}
```

```
#}
```

```
server {
```

```
listen 80;
```

```
server_name mall-ad.messandbox.com;
```

```
proxy_set_header X-Forwarded-For $remote_addr;  
proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;  
location / {  
    root /data/zte/www/cms/systemCode/publish/www/advert;  
}
```

```

error_page 500 502 503 504 /50x.html;
location = /50x.html {
    root html;
}

}

server {
listen 80;

server_name mall-so.messandbox.com;

charset utf-8;

#access_log /data/logs/b2c2c/access_b_so.log main;
proxy_set_header X-Forwarded-For $remote_addr;
proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
location / {
    root /data/zte/www/static/ecoeco;
    index index.html index.htm;
}

}

server {
listen 80;

server_name mall-se.messandbox.com;

#access_log /data/logs/b2c2c/access_b_se.log main;
proxy_set_header X-Forwarded-For $remote_addr;
proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
location / {
    root /data/zte/www/static/ecec;
    index index.html index.htm;
}

}

server {
listen 80;

server_name mall-img.messandbox.com;

#access_log /data/logs/b2c2c/access_b_img.log main;
proxy_set_header X-Forwarded-For $remote_addr;
proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
location / {
    root /data/zte/www/img;
    index index.html index.htm;
}

error_page 500 502 503 504 /50x.html;

```

```

location = /50x.html {
    root html;
}

}

server {
listen 80;

server_name mall-oimg.messandbox.com;

    #access_log /data/logs/b2c2c/access_b_img.log main;
    proxy_set_header X-Forwarded-For $remote_addr;
    proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
    location / {
        root /data/zte/www/img-bak;
        index index.html index.htm;
    }

    error_page 500 502 503 504 /50x.html;
    location = /50x.html {
        root html;
    }
}

server {
listen 80;

server_name mall-my.messandbox.com;

    #access_log /data/logs/b2c2c/access_b_my.log main;
    proxy_set_header X-Forwarded-For $remote_addr;
    proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
    location / {
        proxy_pass http://mall-my.messandbox.com;
    }
}

server {
listen 80;

server_name mall-pay.messandbox.com;

    #access_log /data/logs/b2c2c/access_b_pay.log main;
    proxy_set_header X-Forwarded-For $remote_addr;
    proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
    location / {
        proxy_pass http://mall-pay.messandbox.com;
    }
}

```

```

error_page 500 502 503 504 /50x.html;
location = /50x.html {
    root html;
}
}

server {
listen 80;
server_name mall-search.messandbox.com;

    #access_log /data/logs/b2c2c/access_b_search.log main;
    proxy_set_header X-Forwarded-For $remote_addr;
    proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
    location / {
        proxy_pass http://mall-search.messandbox.com;
    }
error_page 500 502 503 504 /50x.html;
location = /50x.html {
    root html;
}
}

server {
listen 80;
server_name mall-info.messandbox.com;

    #access_log /data/logs/b2c2c/access_b_info.log main;
    proxy_set_header X-Forwarded-For $remote_addr;
    proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
    location / {
        proxy_pass http://mall-info.messandbox.com;
    }
error_page 500 502 503 504 /50x.html;
location = /50x.html {
    root html;
}
}

server {
listen 80;
server_name mall-sc.messandbox.com;

    #access_log /data/logs/b2c2c/access_b_sc.log main;
    proxy_set_header X-Forwarded-For $remote_addr;
    proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
    location / {

```



```

        proxy_pass http://mall-sc.messandbox.com;
    }
}

server {
listen 80;
server_name mall-open.messandbox.com;

#access_log /data/logs/b2c2c/access_b_open.log main;
proxy_set_header X-Forwarded-For $remote_addr;
proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
location / {
    proxy_pass http://mall-open.messandbox.com;
}
location ~/sindex {
    root /data/zte/www/html/b2c2c;
    index sindex.html;
}
}

server {
listen 80;
server_name mall-cms.messandbox.com;

#access_log /data/logs/b2c2c/access_b_cms.log main;
proxy_set_header X-Forwarded-For $remote_addr;
proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
location / {
    proxy_pass http://mall-cms.messandbox.com;
}
}

server {
listen 80;
server_name mall-common.messandbox.com;

#access_log /data/logs/b2c2c/access_b_common.log main;
proxy_set_header X-Forwarded-For $remote_addr;
proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
location / {
    proxy_pass http://mall-common.messandbox.com;
}
}

server {

```

```

listen 80;
server_name mall-cs.messandbox.com;

#access_log /data/logs/b2c2c/access_b_cs.log main;
proxy_set_header X-Forwarded-For $remote_addr;
proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
location / {
    proxy_pass http://mall-cs.messandbox.com;
}
}

server {
listen 80;
server_name mall-www.messandbox.com;
#access_log /data/logs/b2c2c/access_b_mall.log main;
error_page 404 = /404.html;
location / {
root /data/zte/www/html/b2c2c;
index sindex/sindex.html sindex/sindex.htm;
}
location /* {
error_page 404 = /404.html;
}
}

server {
listen 80;
server_name mall-s.messandbox.com;

#access_log /data/logs/b2c2c/access_b_mall.log main;
proxy_set_header X-Forwarded-For $remote_addr;
proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
location / {
    root /data/zte/www/static/b2c2c;
    index index.html index.htm;
}
}

server {
listen 80;
server_name mall-c.messandbox.com;

```

```
#access_log /data/logs/b2c2c/access_b_mall.log main;
proxy_set_header X-Forwarded-For $remote_addr;
proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
```

```
location / {
    proxy_pass http://mall-c.messandbox.com;
}
```

```
}
server {
listen 80;
server_name mall-download.messandbox.com;
```

```
proxy_set_header X-Forwarded-For $remote_addr;
proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
```

```
location / {
    root /data/zte/www/downloads;
    index index.html index.htm;
}
```

```
}</pre>
```

```
<p>tomcat_catalina.sh</p>
```

```
<pre class="brush: java">JAVA_OPTS='-server -Xms2048m -Xmx2048m -Xss256k -XX:MaxN
wSize=256m -XX:MaxPermSize=256m'</pre>
```

```
<p>tomcat_app_server.xml</p>
```

```
<pre class="brush: java">    &lt;Executor name="tomcatThreadPool" namePrefix="catalina-e
ec-"
```

```
        maxThreads="3000" minSpareThreads="500" maxIdleTime="60000"/&gt;
```

```
&lt;Connector executor="tomcatThreadPool" port="8091" protocol="org.apache.coyote.http
1.1.Http11NioProtocol"
```

```
connectionTimeout="20000"
```

```
keepAliveTimeout="15000"
```

```
maxKeepAliveRequests="1"
```

```
acceptCount="1000"
```

```
enableLookups="false"
```

```
redirectPort="8443" URIEncoding="UTF-8" /&gt;
```

```
&lt;Host name="mall-sc.messandbox.com" appBase="/data/tomcat-m-web/webapps/cm-co
kie-web" unpackWARs="true" autoDeploy="true" xmlValidation="false" xmlNamespaceAwar
="false"&gt;
```

```
&lt;Context docBase="/data/tomcat-m-web/webapps/cm-cookie-web" path="/" reloadabl
="true"/&gt;
```

```
&lt;/Host&gt;
```

```
&lt;Host name="mall-my.messandbox.com" appBase="/data/tomcat-m-web/webapps/cm-m
```

```
member-web" unpackWARS="true" autoDeploy="true" xmlValidation="false" xmlNamespaceAware="false">
<Context docBase="/data/tomcat-m-web/webapps/cm-member-web" path="" reloadable="true"/>
</Host>
<Host name="mall-info.messandbox.com" appBase="/data/tomcat-m-web/webapps/cm-info-web" unpackWARS="true" autoDeploy="true" xmlValidation="false" xmlNamespaceAware="false">
<Context docBase="/data/tomcat-m-web/webapps/cm-info-web" path="" reloadable="true"/>
</Host>
<Host name="mall-open.messandbox.com" appBase="/data/tomcat-m-web/webapps/cm-open-web" unpackWARS="true" autoDeploy="true" xmlValidation="false" xmlNamespaceAware="false">
<Context docBase="/data/tomcat-m-web/webapps/cm-open-web" path="" reloadable="true"/>
</Host>
<Host name="mall-pay.messandbox.com" appBase="/data/tomcat-m-web/webapps/cm-pay-web" unpackWARS="true" autoDeploy="true" xmlValidation="false" xmlNamespaceAware="false">
<Context docBase="/data/tomcat-m-web/webapps/cm-pay-web" path="" reloadable="true"/>
</Host>
<Host name="mall-cms.messandbox.com" appBase="/data/tomcat-m-web/webapps/cm-cms-web" unpackWARS="true" autoDeploy="true" xmlValidation="false" xmlNamespaceAware="false">
<Context docBase="/data/tomcat-m-web/webapps/cm-cms-web" path="" reloadable="true"/>
</Host>
<Host name="mall-common.messandbox.com" appBase="/data/tomcat-m-web/webapps/cm-common-web" unpackWARS="true" autoDeploy="true" xmlValidation="false" xmlNamespaceAware="false">
<Context docBase="/data/tomcat-m-web/webapps/cm-common-web" path="" reloadable="true"/>
</Host>
<Host name="mall-cs.messandbox.com" appBase="/data/tomcat-m-web/webapps/cm-community-service-web" unpackWARS="true" autoDeploy="true" xmlValidation="false" xmlNamespaceAware="false">
<Context docBase="/data/tomcat-m-web/webapps/cm-community-service-web" path="" reloadable="true"/>
</Host>
<Host name="mall-c.messandbox.com" appBase="/data/tomcat-m-web/webapps/cm-cookie-web" unpackWARS="true" autoDeploy="true" xmlValidation="false" xmlNamespaceAware="false">
```

```
&lt;Context docBase="/data/tomcat-m-web/webapps/cm-cookie-web" path="" reloadabl
="true"/&gt;
```

```
&lt;/Host&gt;
```

```
&lt;Host name="mall-search.messandbox.com" appBase="/data/tomcat-m-web/webapps/cm
search-web" unpackWARs="true" autoDeploy="true" xmlValidation="false" xmlNamespaceA
re="false"&gt;
```

```
&lt;Context docBase="/data/tomcat-m-web/webapps/cm-search-web" path="" reloadabl
="true"/&gt;
```

```
&lt;/Host&gt; </pre>
```

```
<p>tomcat_web_server.xml</p>
```

```
<pre class="brush: java">JAVA_OPTS='-server -Xms512m -Xmx1536m -Xss512k -XX:MaxNe
Size=512m -XX:MaxPermSize=512m -Djava.awt.headless=true'
```

```
&lt;Executor name="tomcatThreadPool" namePrefix="catalina-exec-"
maxThreads="3000" minSpareThreads="500"/&gt;
```

```
&lt;Connector executor="tomcatThreadPool" port="7891" protocol="org.apache.coyote.http
1.1.Http11NioProtocol"
```

```
connectionTimeout="20000"
```

```
maxThreads="3000"
```

```
minSpareThreads="200"
```

```
maxSpareThreads="5000"
```

```
acceptCount="5000"
```

```
enableLookups="false"
```

```
redirectPort="8443" URIEncoding="UTF-8"/&gt;
```

```
&lt;Context docBase="/data/tomcat-m-app/webapps/cm-cms-app" path="/cm-cms-app"
debug="0" reloadable="true" /&gt;
```

```
&lt;Context docBase="/data/tomcat-m-app/webapps/cm-common-app" path="/cm-com
on-app" debug="0" reloadable="true" /&gt;
```

```
&lt;Context docBase="/data/tomcat-m-app/webapps/cm-community-service-app" path="
cm-sommunity-service-app" debug="0" reloadable="true" /&gt;
```

```
&lt;Context docBase="/data/tomcat-m-app/webapps/cm-info-app" path="/cm-info-app"
debug="0" reloadable="true" /&gt;
```

```
&lt;Context docBase="/data/tomcat-m-app/webapps/cm-member-app" path="/cm-mem
er-app" debug="0" reloadable="true" /&gt;
```

```
&lt;Context docBase="/data/tomcat-m-app/webapps/cm-open-app" path="/cm-open-app"
debug="0" reloadable="true" /&gt;
```

```
&lt;Context docBase="/data/tomcat-m-app/webapps/cm-pay-app" path="/cm-pay-app"
debug="0" reloadable="true" /&gt;
```

```
&lt;Context docBase="/data/tomcat-m-app/webapps/cm-search-app" path="/cm-search-
pp" debug="0" reloadable="true" /&gt;
```

```
</pre>
```

```
<p>&nbsp;&nbsp;&nbsp;</p>
```

```
<p>&nbsp;&nbsp;&nbsp;</p>
```

