



链滴

linux 根据端口号查找对应的程序目录

作者: [huihui](#)

原文链接: <https://ld246.com/article/1488351684461>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

1: 根据端口号查找对应的进程id

```
(1): [root@192 local]# lsof -i:6122
```

```
COMMAND  PID USER  FD  TYPE  DEVICE SIZE/OFF NODE NAME
```

```
java    22775 root   42u IPv6  7350952    0t0  TCP *:bex-webadmin (LISTEN)
```

```
[root@192 local]#
```

```
(2): [root@192 local]# netstat -apn|grep 6122
```

```
tcp      0    0 :::6122          :::*              LISTEN          22775/java
```

```
[root@192 local]#
```

得到进程id = 22775

2: 根据进程id查找程序目录

```
[root@192 local]# cat /proc/22775/environ
```

```
HOSTNAME=192.168.45.35TERM=xterm-newSHELL=/bin/bashHISTSIZ=1000SSH_CLIENT=1  
2.168.41.121 51588 22QTDIR=/usr/lib64/qt-3.3QTINC=/usr/lib64/qt-3.3/includeSSH_TTY=/de  
/pts/0USER=rootLS_COLORS=MAVEN_HOME=/opt/maven/apache-maven-3.2.2MAIL=/var/s  
ool/mail/rootPATH=/usr/lib64/qt-3.3/bin:/usr/kerberos/sbin:/usr/kerberos/bin:/usr/local/sbin  
/usr/local/bin:/sbin:/bin:/usr/sbin:/usr/bin:/opt/maven/apache-maven-3.2.2/bin:/root/bin **  
WD=/usr/local/src/tomcat7x/bin** KDE_IS_PRELINKED=1LANG=zh_CN.UTF-8KDEDIRS=/usrS  
H_ASKPASS=/usr/libexec/openssh/gnome-ssh-askpassHISTCONTROL=ignoredupsSHLVL=2  
OME=/rootLOGNAME=rootQTLIB=/usr/lib64/qt-3.3/libCVS_RSH=sshSSH_CONNECTION=192  
168.41.121 51588 192.168.45.35 22LESSOPEN=|/usr/bin/lesspipe.sh %sHISTTIMEFORMAT=%F  
%T root G_BROKEN_FILENAMES=1_/opt/jdk1.7.0_15/bin/java[root@192 local]#
```

得到目录地址PWD=/usr/local/src/tomcat7x/bin