



链滴

Mybatis 简单的一个小问题

作者: [kevin2020](#)

原文链接: <https://ld246.com/article/1496828094503>

来源网站: 链滴

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

```

<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE mapper
PUBLIC "-//mybatis.org//DTD Mapper 3.0//EN"
"http://mybatis.org/dtd/mybatis-3-mapper.dtd">
<mapper namespace="com.kevin2020.dao.ConcernMapper">
<insert id="insertConcern" parameterType="int">
    insert into tb_concern(userId,concernId) values(#{0},#{1})
</insert>
</mapper>

package com.kevin2020.dao;

import org.apache.ibatis.annotations.Param;

public interface ConcernMapper {
    void insertConcern(int userId,int concernId);
    // void insertConcern(@Param("userId")int userId,@Param("concernId")int concernId);
}

@Test
public void testConcern(){
    concernMapper.insertConcern(6, 3);
}

```

nested exception is org.apache.ibatis.binding.BindingException: Parameter 'agr0' not found. Available parameters are [arg1, arg0, param1, param2]

绑定参数的方式可以成功

为什么#{0}这种方式会失败求解