



链滴

mysql 修改端口经验

作者: [gentoo666](#)

原文链接: <https://ld246.com/article/1497188038243>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

mysql更改端口

修改/etc/my.cnf

添加port=3308

修改后如下

```
[mysqld]
```

```
datadir=/var/lib/mysql
```

```
socket=/var/lib/mysql/mysql.sock
```

```
port=3308
```

```
user=mysql
```

Disabling symbolic-links is recommended to prevent assorted security risks

```
symbolic-links=0
```

```
default-character-set=utf8
```

```
[mysqld_safe]
```

```
log-error=/var/log/mysql.log
```

```
pid-file=/var/run/mysql/mysql.pid
```

然后重启mysql

如果你开启了selinux, mysql会无法启动, 你会在日志中看到以下错误

```
[ERROR] Can't start server: Bind on TCP/IP port: Permission denied
```

```
[ERROR] Do you already have another mysqld server running on port: 3308
```

那么, 你需要关掉selinux, 不想重启服务器, 而关掉selinux, 使用以下命令

```
/usr/sbin/setenforce 0
```

修改linux下mysql端口时候报错:

```
Can't start server: Bind on TCP/IP port: Permission denied
```

需要修改: vi /etc/selinux/config

```
SELINUX=disabled
```

然后重启服务器即可