



链滴

Redis 的安装和一些常用指令

作者: [seanlee](#)

原文链接: <https://ld246.com/article/1499394194137>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)


```
</div>
<ol>
<li style="list-style-type: decimal; list-style-position: inside; white-space: pre-wrap; text-align:
eft; line-height: 1.75; font-size: 14px;">//&nbsp;&nbsp;&nbsp;初始化redis连接&nbsp;&nbsp;&nbsp;</li>
<li style="list-style-type: decimal; list-style-position: inside; white-space: pre-wrap; text-align:
eft; line-height: 1.75; font-size: 14px;">Jedis&nbsp;&nbsp;jedis&nbsp;&nbsp;=&nbsp;&nbsp;new&nbsp;&nbsp;Jedis("ip",
379);&nbsp;&nbsp;&nbsp;</li>
</ol>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">&nbsp;&nbsp;&nbsp;
</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">2.设定
据格式</div>
<ol>
<li style="list-style-type: decimal; list-style-position: inside; white-space: pre-wrap; text-align:
eft; line-height: 1.75; font-size: 14px;">jedis.set("username",&nbsp;&nbsp;"myjedis");&nbsp;&nbsp;&nbsp;<
li>
<li style="list-style-type: decimal; list-style-position: inside; white-space: pre-wrap; text-align:
eft; line-height: 1.75; font-size: 14px;">System.out.println(jedis.get("username"));&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;
</li>
</ol>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">&nbsp;&nbsp;&nbsp;
</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">#查看
有key</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">keys *
keys "*" </div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">&nbsp;&nbsp;&nbsp;
</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">#刷新
前缓存</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">flushall
</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">&nbsp;&nbsp;&nbsp;
</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">#授权<
div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">auth +
户名</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">&nbsp;&nbsp;&nbsp;
</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">#删除
个key</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">del key
</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">&nbsp;&nbsp;&nbsp;
</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">#设置
期时间 expire</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">&nbsp;&nbsp;&nbsp;
</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">#查看
配前缀的keys</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">keys "m
ao*" </div>
```

```
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">&nbsp;/div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">#清空re
is</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">flushdb
/dv>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">&nbsp;/div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">#随机
出一个key</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">random
ey</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">&nbsp;/div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">#查看ke
的类型</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">type ke
</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">&nbsp;/div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">#查看
数据库中key的数量</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">dbsize<
div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">&nbsp;/div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">#查看
务器信息</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">info</d
v>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">&nbsp;/div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">#查看re
is正在做什么</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">monito
</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">&nbsp;/div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">#查看
志</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">slowlog
get</div>
<div style="white-space: pre-wrap; text-align: left; line-height: 1.75; font-size: 14px;">slowlog
get 10</div>
```