

Linux 搭建 SVN

作者: [kenan](#)

原文链接: <https://ld246.com/article/1508594598589>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

```
<pre class="prettyprint lang-bsh">#1.下载svn
wget http://apache.fayea.com/subversion/subversion-1.9.5.tar.gz

#2.解压tar.gz并进入
tar -zxvf ./subversion-1.9.5.tar.gz
cd ./subversion-1.9.5

#3.编译
./configure --prefix=/home/program/subversion-1.9.5
提示
configure: error: no suitable APR found

#4.安装apr
wget http://mirror.bit.edu.cn/apache//apr/apr-1.5.2.tar.gz
tar -zxvf ./apr-1.5.2.tar.gz
cd apr-1.5.2.tar.gz
./configure --prefix=/home/program/apr-1.5.2
make
make install

#5.安装apr-util
wget http://mirror.bit.edu.cn/apache//apr/apr-util-1.5.4.tar.gz
tar -zxvf ./apr-util-1.5.4.tar.gz
cd ./apr-util-1.5.4
./configure --prefix=/home/program/apr-util-1.5.4 --with-apr=/home/program/apr-1.5.2/
make
make install

#6.进入subversion
cd ./subversion-1.9.5

#7.安装sqlite
wget http://www.sqlite.org/sqlite-amalgamation-3071501.zip
unzip sqlite-amalgamation-3071501.zip
mv ./sqlite-amalgamation-3071501 ./sqlite-amalgamation-3071501 ./subversion-1.9.5/sqlite-
malgamation

#7.安装
./configure --prefix=/home/program/subversion-1.9.5 --with-apr=/home/program/apr-1.5.2/
--with-apr-util=/home/program/apr-util-1.5.4/
make
make install

#8.配置环境变量
vi /etc/profile
SVN_HOME=/opt/subversion
export PATH=$PATH:$SVN_HOME/bin
#source /etc/profile (刷新设置, 避免重启)
#echo $PATH (查看设置是否生效)

#9.测试是否成功
svnserve --version
```

#10.

</pre>