



链滴

Spark 的三种参数配置

作者: [rxz](#)

原文链接: <https://ld246.com/article/1513238077250>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

<h2 id="一-spark-defaults-conf">一、 spark-defaults.conf</h2>

<pre> <code class="highlight-chroma"> Example:

 spark.master
spark://master:7077
 spark.eventLog.
nabled true
 spark.eventLog
dir hdfs://namenode:8021/directory
 spark.serializer
org.apache.spark.serializer.KryoSerializer
 spark.driver.m
emory 5g
 spark.executor.
extraJavaOptions -XX:+PrintGCDetails -Dkey=value -Dnumbers="one two three"

 </code> </pre>

<h2 id="二-spark-submit">二、 spark submit</h2>

<pre> <code class="highlight-chroma"> ./bin/spark-submit
 --name "My app"
 --master local[4]
 --conf spark.shuff
e.spill=false
 --conf "spark.exec
tor.extraJavaOptions=-XX:+PrintGCDetails -XX:+PrintGCTimeStamps" myApp.jar
 </code> </pre>

<h2 id="三-sparkconf">三、 sparkconf</h2>

<pre> <code class="highlight-chroma"> SparkConf conf = new SparkConf()
 .setMaster("l
cal[*]")
 .setAppName
"sqlVsDsl")
 .set("spark.ex
cutor.memory", "1g");
 </code> </pre>