



链滴

CommonLang3 中的 StringUtils 最全解析

作者: [mingan](#)

原文链接: <https://ld246.com/article/1515654670647>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

`public static boolean isEmpty()` <https://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStringUtils.html%23line.208> `isEmpty()` [https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%3Dtrue](https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%3Dtrue "class or interface in java.lang") `CharSequence`

常用函数之一，判断字符串是否为 "" 或者 null

```
StringUtils.isEmpty(null)    = true  
StringUtils.isEmpty("")     = true  
StringUtils.isEmpty(" ")    = false  
StringUtils.isEmpty("bob")  = false  
StringUtils.isEmpty(" bob ") = false
```

`public static boolean isEmpty()` <https://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStringUtils.html%23line.227> `isEmpty()` [https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%3Dtrue](https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%3Dtrue "class or interface in java.lang") `CharSequence`

最常用函数之一，跟上面方法相对

```
StringUtils.isNotEmpty(null) = false  
StringUtils.isNotEmpty("")   = false  
StringUtils.isNotEmpty(" ")  = true  
StringUtils.isNotEmpty("bob") = true  
StringUtils.isNotEmpty(" bob ") = true
```

`public static boolean isEmpty()` <https://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStringUtils.html%23line.248> `isEmpty()` [https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%3Dtrue](https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%3Dtrue "class or interface in java.lang") `CharSequence` ... `css`

任意一个参数为空的话，返回 true

如果这些参数都不为空的话返回 false。

在写一些判断条件的时候，这个方法还是很实用的。

```
StringUtils.isEmpty(null, "foo") = true  
StringUtils.isEmpty("", "bar")  = true  
StringUtils.isEmpty("bob", "")  = true  
StringUtils.isEmpty(" bob ", null) = true  
StringUtils.isEmpty(" ", "bar")  = false  
StringUtils.isEmpty("foo", "bar") = false
```

`public static boolean isEmpty()` <https://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStringUtils.html%23line.277> `isEmpty()` [https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%3Dtrue](https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%3Dtrue "class or interface in java.lang") `CharSequence` ... `css`

任意一个参数是空，返回 false

所有参数都不为空，返回 true

注意这些方法的用法

```
StringUtils.isEmpty(null) = false
```

```
StringUtils.isEmpty(null, "foo")    = false<br>
StringUtils.isEmpty("", "bar")      = false<br>
StringUtils.isEmpty("bob", "")      = false<br>
StringUtils.isEmpty(" bob ", null)  = false<br>
StringUtils.isEmpty(" ", "bar")     = true<br>
StringUtils.isEmpty("foo", "bar")   = true</p>
<p>public static boolean <a href="https://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStringUtils.html%23line.296" target="_blank" rel="nofollow ugc">isEmpty</a>(<a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%3Dtrue" title="class or interface in java.lang" target="_blank" rel="nofollow ugc">CharSequence</a> cs)</p>
<p>判断字符对象是不是空字符串，注意与 isEmpty 的区别</p>
<p>StringUtils.isBlank(null)        = true<br>
StringUtils.isBlank("")           = true<br>
StringUtils.isBlank(" ")          = true<br>
StringUtils.isBlank("bob")        = false<br>
StringUtils.isBlank(" bob ")      = false</p>
<p>public static boolean <a href="https://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStringUtils.html%23line.326" target="_blank" rel="nofollow ugc">isNotBlank</a>(<a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%3Dtrue" title="class or interface in java.lang" target="_blank" rel="nofollow ugc">CharSequence</a> cs)</p>
<p>StringUtils.isNotBlank(null)     = false<br>
StringUtils.isNotBlank("")         = false<br>
StringUtils.isNotBlank(" ")       = false<br>
StringUtils.isNotBlank("bob")     = true<br>
StringUtils.isNotBlank(" bob ")   = true</p>
<p>原理同上</p>
<p>public static boolean <a href="https://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStringUtils.html%23line.348" target="_blank" rel="nofollow ugc">isAnyBlank</a>(<a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%3Dtrue" title="class or interface in java.lang" target="_blank" rel="nofollow ugc">CharSequence</a>... cs)</p>
<p>StringUtils.isAnyBlank(null)      = true<br>
StringUtils.isAnyBlank(null, "foo") = true<br>
StringUtils.isAnyBlank(null, null)  = true<br>
StringUtils.isAnyBlank("", "bar")   = true<br>
StringUtils.isAnyBlank("bob", "")   = true<br>
StringUtils.isAnyBlank(" bob ", null) = true<br>
StringUtils.isAnyBlank(" ", "bar")  = true<br>
StringUtils.isAnyBlank("foo", "bar") = false</p>
<p>public static boolean <a href="https://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStringUtils.html%23line.378" target="_blank" rel="nofollow ugc">isNoneBlank</a>(<a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%3Dtrue" title="class or interface in java.lang" target="_blank" rel="nofollow ugc">CharSequence</a>... cs)</p>
```

```

<p>StringUtils.isNoneBlank(null)          = false<br>
StringUtils.isNoneBlank(null, "foo")    = false<br>
StringUtils.isNoneBlank(null, null)     = false<br>
StringUtils.isNoneBlank("", "bar")      = false<br>
StringUtils.isNoneBlank("bob", "")      = false<br>
StringUtils.isNoneBlank(" bob ", null)  = false<br>
StringUtils.isNoneBlank(" ", "bar")     = false<br>
StringUtils.isNoneBlank("foo", "bar")   = true</p>
<p>public static <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.co
%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title
"class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a> <a href="http
://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-
ang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStr
ngUtils.html%23line.407" target="_blank" rel="nofollow ugc">trim</a>(<a href="https://ld2
6.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fja
a%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang" target=
_blank" rel="nofollow ugc">String</a> str)</p>
<p>移除字符串两端的空字符串，制表符 char &lt;= 32 如：\n\t</p>
<p>如果为空的话，返回空</p>
<p>如果为""</p>
<p>StringUtils.trim(null)                = null<br>
StringUtils.trim("")                   = ""<br>
StringUtils.trim(" ")                  = ""<br>
StringUtils.trim("abc")                 = "abc"<br>
StringUtils.trim(" abc ")              = "abc"</p>
<p>变体有</p>
<p>public static <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.co
%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title
"class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a> <a href="http
://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-
ang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStr
ngUtils.html%23line.433" target="_blank" rel="nofollow ugc">trimToNull</a>(<a href="https
//ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fap
%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang"
arget="_blank" rel="nofollow ugc">String</a> str)</p>
<p>public static <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.co
%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title
"class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a> <a href="http
://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-
ang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStr
ngUtils.html%23line.459" target="_blank" rel="nofollow ugc">trimToEmpty</a>(<a href="ht
tps://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2F
pi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang
target="_blank" rel="nofollow ugc">String</a> str)</p>
<p>不常用，跟 trim()方法类似</p>
<p>public static <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.co
%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title
"class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a> <a href="http
://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-
ang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStr
ngUtils.html%23line.487" target="_blank" rel="nofollow ugc">strip</a>(<a href="https://ld2
6.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fja
a%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang" target=
_blank" rel="nofollow ugc">String</a> str)</p>

```

```
<p>public static <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.co
%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title
"class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a> <a href="http
://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-
lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStr
ngUtils.html%23line.574" target="_blank" rel="nofollow ugc">strip</a> (<a href="https://ld2
6.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fja
a%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang" target=
_blank" rel="nofollow ugc">String</a> str,<br>
<a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7
2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface
in java.lang" target="_blank" rel="nofollow ugc">String</a> stripChars)</p>
<p>str: 被处理的字符串, 可为空</p>
<p>stripChars: 删除的字符串, </p>
<p>StringUtils.strip(null, *)      = null<br>
StringUtils.strip("", *)          = ""<br>
StringUtils.strip("abc", null)    = "abc"<br>
StringUtils.strip(" abc", null)   = "abc"<br>
StringUtils.strip("abc ", null)   = "abc"<br>
StringUtils.strip(" abc ", null)  = "abc"<br>
StringUtils.strip(" abcxy", "xyz") = " abc"</p>
<p>public static boolean <a href="https://ld246.com/forward?goto=http%3A%2F%2Fcomm
ns.apache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg
2Fapache%2Fcommons%2Flang3%2FStringUtils.html%23line.784" target="_blank" rel="nofol
ow ugc">equals</a> (<a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle
.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%
Dtrue" title="class or interface in java.lang" target="_blank" rel="nofollow ugc">CharSequen
e</a> cs1,<br>
<a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7
2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%3Dtrue" title="class or
nterface in java.lang" target="_blank" rel="nofollow ugc">CharSequence</a> cs2)</p>
<p>字符串比对方法, 是比较实用的方法之一, 两个比较的字符串都能为空, 不会报空指针异常。 </
>
<p>StringUtils.equals(null, null)  = true<br>
StringUtils.equals(null, "abc")  = false<br>
StringUtils.equals("abc", null)  = false<br>
StringUtils.equals("abc", "abc") = true<br>
StringUtils.equals("abc", "ABC") = false</p>
<p>public static boolean <a href="https://ld246.com/forward?goto=http%3A%2F%2Fcomm
ns.apache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg
2Fapache%2Fcommons%2Flang3%2FStringUtils.html%23line.818" target="_blank" rel="nofol
ow ugc">equalsIgnoreCase</a> (<a href="https://ld246.com/forward?goto=http%3A%2F%2
docs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fi
-external%3Dtrue" title="class or interface in java.lang" target="_blank" rel="nofollow ugc">
harSequence</a> str1,<br>
<a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7
2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%3Dtrue" title="class or
nterface in java.lang" target="_blank" rel="nofollow ugc">CharSequence</a> str2)</p>
<p>上面方法的变体</p>
<p>字符串比较 (忽略大小写), 在验证码.....等字符串比较, 真是很实用。 </p>
<p>StringUtils.equalsIgnoreCase(null, null)  = true<br>
StringUtils.equalsIgnoreCase(null, "abc")  = false<br>
StringUtils.equalsIgnoreCase("abc", null)  = false<br>
StringUtils.equalsIgnoreCase("abc", "abc") = true<br>
```

```

StringUtils.equalsIgnoreCase("abc", "ABC") = true</p>
<p>public static int <a href="https://ld246.com/forward?goto=http%3A%2F%2Fcommons.a
ache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fa
ache%2Fcommons%2Flang3%2FStringUtils.html%23line.852" target="_blank" rel="nofollow
gc">indexOf</a>(<a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.c
om%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%3D
true" title="class or interface in java.lang" target="_blank" rel="nofollow ugc">CharSequence
/a> seq,<br>
int searchChar)</p>
<p>indexOf 这个方法不必多说，这个方法主要处理掉了空字符串的问题，不会报空指针，有一定用
</p>
<p>StringUtils.indexOf(null, *)      = -1<br>
StringUtils.indexOf("", *)          = -1<br>
StringUtils.indexOf("aabaabaa", 'a') = 0<br>
StringUtils.indexOf("aabaabaa", 'b') = 2</p>
<p>public static int <a href="https://ld246.com/forward?goto=http%3A%2F%2Fcommons.a
ache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fa
ache%2Fcommons%2Flang3%2FStringUtils.html%23line.997" target="_blank" rel="nofollow
gc">ordinalIndexOf</a>(<a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.or
acle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-externa
%3Dtrue" title="class or interface in java.lang" target="_blank" rel="nofollow ugc">CharSequ
nce</a> str,<br>
<a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7
2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%3Dtrue" title="class or
nterface in java.lang" target="_blank" rel="nofollow ugc">CharSequence</a> searchStr,<br>
int ordinal)</p>
<p>字符串在另外一个字符串里，出现第 Ordinal 次的位置</p>
<p>StringUtils.ordinalIndexOf(null, *, <em> )      = -1<br>
StringUtils.ordinalIndexOf(</em>, null, *)        = -1<br>
StringUtils.ordinalIndexOf("", "", *)             = 0<br>
StringUtils.ordinalIndexOf("aabaabaa", "a", 1)    = 0<br>
StringUtils.ordinalIndexOf("aabaabaa", "a", 2)    = 1<br>
StringUtils.ordinalIndexOf("aabaabaa", "b", 1)    = 2<br>
StringUtils.ordinalIndexOf("aabaabaa", "b", 2)    = 5<br>
StringUtils.ordinalIndexOf("aabaabaa", "ab", 1)   = 1<br>
StringUtils.ordinalIndexOf("aabaabaa", "ab", 2)   = 4<br>
StringUtils.ordinalIndexOf("aabaabaa", "", 1)     = 0<br>
StringUtils.ordinalIndexOf("aabaabaa", "", 2)     = 0</p>
<p>public static int <a href="https://ld246.com/forward?goto=http%3A%2F%2Fcommons.a
ache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fa
ache%2Fcommons%2Flang3%2FStringUtils.html%23line.1143" target="_blank" rel="nofollow
ugc">lastIndexOf</a>(<a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.orac
e.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external
3Dtrue" title="class or interface in java.lang" target="_blank" rel="nofollow ugc">CharSeque
ce</a> seq,<br>
int searchChar)</p>
<p>字符串最后一次出现的位置</p>
<p>StringUtils.lastIndexOf(null, *)      = -1<br>
StringUtils.lastIndexOf("", *)          = -1<br>
StringUtils.lastIndexOf("aabaabaa", 'a') = 7<br>
StringUtils.lastIndexOf("aabaabaa", 'b') = 5</p>
<p>public static int <a href="https://ld246.com/forward?goto=http%3A%2F%2Fcommons.a
ache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fa
ache%2Fcommons%2Flang3%2FStringUtils.html%23line.1252" target="_blank" rel="nofollow

```

```
ugc">lastOrdinalIndexOf</a>( <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdcs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%3Dtrue" title="class or interface in java.lang" target="_blank" rel="nofollow ugc">CharSequence</a> str, <br>
<a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%3Dtrue" title="class or interface in java.lang" target="_blank" rel="nofollow ugc">CharSequence</a> searchStr, <br>
int ordinal) </p>
<p>字符串 searchStr 在 str 里面出现倒数第 ordinal 出现的位置</p>
<p>StringUtils.lastOrdinalIndexOf(null, *, <em> ) = -1<br>
StringUtils.lastOrdinalIndexOf(</em>, null, *) = -1<br>
StringUtils.lastOrdinalIndexOf("", "", *) = 0<br>
StringUtils.lastOrdinalIndexOf("aabaabaa", "a", 1) = 7<br>
StringUtils.lastOrdinalIndexOf("aabaabaa", "a", 2) = 6<br>
StringUtils.lastOrdinalIndexOf("aabaabaa", "b", 1) = 5<br>
StringUtils.lastOrdinalIndexOf("aabaabaa", "b", 2) = 2<br>
StringUtils.lastOrdinalIndexOf("aabaabaa", "ab", 1) = 4<br>
StringUtils.lastOrdinalIndexOf("aabaabaa", "ab", 2) = 1<br>
StringUtils.lastOrdinalIndexOf("aabaabaa", "", 1) = 8<br>
StringUtils.lastOrdinalIndexOf("aabaabaa", "", 2) = 8</p>
<p>public static boolean <a href="https://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang%3%2FStringUtils.html%23line.1405" target="_blank" rel="nofollow ugc">contains</a>( <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%3Dtrue" title="class or interface in java.lang" target="_blank" rel="nofollow ugc">CharSequence</a> seq, <br>
int searchChar) </p>
<p>字符串 seq 是否包含 searchChar</p>
<p>StringUtils.contains(null, *) = false<br>
StringUtils.contains("", *) = false<br>
StringUtils.contains("abc", 'a') = true<br>
StringUtils.contains("abc", 'z') = false</p>
<p>public static boolean <a href="https://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang%3%2FStringUtils.html%23line.1608" target="_blank" rel="nofollow ugc">containsAny</a>( <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external%3Dtrue" title="class or interface in java.lang" target="_blank" rel="nofollow ugc">CharSequence</a> cs, <br>
char... searchChars) </p>
<p>包含后面数组中的任意对象, 返回 true</p>
<p>StringUtils.containsAny(null, <em> ) = false<br>
StringUtils.containsAny("", <em> ) = false<br>
StringUtils.containsAny(</em>, null) = false<br>
StringUtils.containsAny(</em>, []) = false<br>
StringUtils.containsAny("zzabyycdxx", ['z', 'a']) = true<br>
StringUtils.containsAny("zzabyycdxx", ['b', 'y']) = true<br>
StringUtils.containsAny("aba", ['z']) = false</p>
<p>public static <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a> <a href="http://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang%3%2FStr
```

```
ngUtils.html%23line.2088" target="_blank" rel="nofollow ugc">substring</a>(<a href="https
//ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fap
%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang"
arget="_blank" rel="nofollow ugc">String</a> str,<br>
int start)</p>
<p>字符串截取</p>
<p>StringUtils.substring(null, *) = null<br>
StringUtils.substring("", *) = ""<br>
StringUtils.substring("abc", 0) = "abc"<br>
StringUtils.substring("abc", 2) = "c"<br>
StringUtils.substring("abc", 4) = ""<br>
StringUtils.substring("abc", -2) = "bc"<br>
StringUtils.substring("abc", -4) = "abc"</p>
<p>public static <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.co
%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title
"class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a> <a href="http
://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-
ang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStr
ngUtils.html%23line.2198" target="_blank" rel="nofollow ugc">left</a>(<a href="https://ld2
6.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fja
a%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang" target=
_blank" rel="nofollow ugc">String</a> str,<br>
int len)</p>
<p>public static <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.co
%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title
"class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a> <a href="http
://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-
ang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStr
ngUtils.html%23line.2231" target="_blank" rel="nofollow ugc">right</a>(<a href="https://ld
46.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fj
va%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang" targe
="_blank" rel="nofollow ugc">String</a> str,<br>
int len)</p>
<p>public static <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.co
%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title
"class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a> <a href="http
://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-
ang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStr
ngUtils.html%23line.2269" target="_blank" rel="nofollow ugc">mid</a>(<a href="https://ld
46.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fj
va%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang" targe
="_blank" rel="nofollow ugc">String</a> str,<br>
int pos,<br>
int len)</p>
<p>这三个方法类似都是截取字符串</p>
<p>public static <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.co
%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title
"class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a>[] <a href="ht
ps://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommon
-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FS
ringUtils.html%23line.2656" target="_blank" rel="nofollow ugc">split</a>(<a href="https://l
246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2F
ava%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang" targe
="_blank" rel="nofollow ugc">String</a> str,<br>
```


[String](https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue "class or interface in java.lang") separatorChars)

字符串分割

```
StringUtils.split(null, *) = null  
StringUtils.split("", *) = []  
StringUtils.split("abc def", null) = ["abc", "def"]  
StringUtils.split("abc def", " ") = ["abc", "def"]  
StringUtils.split("abc def", " ") = ["abc", "def"]  
StringUtils.split("ab:cd:ef", ":") = ["ab", "cd", "ef"]
```

public static [String](https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue "class or interface in java.lang") [join](http://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStringUtils.html%23line.3302)(T... elements)

字符串连接

```
StringUtils.join(null) = null  
StringUtils.join([]) = ""  
StringUtils.join([null]) = ""  
StringUtils.join(["a", "b", "c"]) = "abc"  
StringUtils.join([null, "", "a"]) = "a"
```

public static [String](https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue "class or interface in java.lang") [join](http://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStringUtils.html%23line.3328)([Object](https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FObject.html%3Fis-external%3Dtrue "class or interface in java.lang") [] array, char separator)

特定字符串连接数组，很多情况下还是蛮实用，不用自己取拼字符串

```
StringUtils.join(null, *) = null  
StringUtils.join([], *) = ""  
StringUtils.join([null], *) = ""  
StringUtils.join(["a", "b", "c"], ";") = "a;b;c"  
StringUtils.join(["a", "b", "c"], null) = "abc"  
StringUtils.join([null, "", "a"], ";") = ";;a"
```

public static [String](https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue "class or interface in java.lang") [deleteWhitespace](http://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStringUtils.html%23line.4196)([String](https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue "class or interface in java.lang") str)

删除空格

```
StringUtils.deleteWhitespace(null) = null  
StringUtils.deleteWhitespace("") = ""  
StringUtils.deleteWhitespace("abc") = "abc"  
StringUtils.deleteWhitespace(" ab c ") = "abc"
```

public static [String](https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue "class or interface in java.lang") [trim](https://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStringUtils.html%23line.4212)()

```

%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title
"class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a> <a href="http
://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-
ang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStr
ngUtils.html%23line.4240" target="_blank" rel="nofollow ugc">removeStart</a>(<a href="ht
ps://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2F
pi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang
" target="_blank" rel="nofollow ugc">String</a> str,<br>
<a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7
2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface
in java.lang" target="_blank" rel="nofollow ugc">String</a> remove)</p>
<p>删除以特定字符串开头的字符串，如果没有的话，就不删除。</p>
<p>StringUtils.removeStart(null, *)    = null<br>
StringUtils.removeStart("", <em>)    = ""<br>
StringUtils.removeStart(</em>, null)  = *<br>
StringUtils.removeStart("www.domain.com", "www.") = "domain.com"<br>
StringUtils.removeStart("domain.com", "www.")    = "domain.com"<br>
StringUtils.removeStart("www.domain.com", "domain") = "www.domain.com"<br>
StringUtils.removeStart("abc", "")    = "abc"</p>
<p>public static <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.co
%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title
"class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a> <a href="http
://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-
ang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStr
ngUtils.html%23line.5287" target="_blank" rel="nofollow ugc">rightPad</a>(<a href="https:
//ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi
2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang" ta
get="_blank" rel="nofollow ugc">String</a> str,<br>
int size,<br>
char padChar)</p>
<p>生成订单号，的时候还是很实用的。右边自动补齐。</p>
<p>StringUtils.rightPad(null, *, *)    = null<br>
StringUtils.rightPad("", 3, 'z')    = "zzz"<br>
StringUtils.rightPad("bat", 3, 'z') = "bat"<br>
StringUtils.rightPad("bat", 5, 'z') = "batzz"<br>
StringUtils.rightPad("bat", 1, 'z') = "bat"<br>
StringUtils.rightPad("bat", -1, 'z') = "bat"</p>
<p>public static <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.co
%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title
"class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a> <a href="http
://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-
ang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStr
ngUtils.html%23line.5399" target="_blank" rel="nofollow ugc">leftPad</a>(<a href="https://
d246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%
Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang" tar
get="_blank" rel="nofollow ugc">String</a> str,<br>
int size,<br>
char padChar)</p>
<p>左边自动补齐</p>
<p>StringUtils.leftPad(null, *, *)    = null<br>
StringUtils.leftPad("", 3, 'z')    = "zzz"<br>
StringUtils.leftPad("bat", 3, 'z') = "bat"<br>
StringUtils.leftPad("bat", 5, 'z') = "zzbat"<br>
StringUtils.leftPad("bat", 1, 'z') = "bat"<br>

```

```
StringUtils.leftPad("bat", -1, 'z') = "bat" </p>
<p>public static <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.co
%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title
"class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a> <a href="http
://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-
ang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStr
ngUtils.html%23line.5507" target="_blank" rel="nofollow ugc">center</a>(<a href="https://
d246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%
Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang" tar
get="_blank" rel="nofollow ugc">String</a> str,<br>
int size)</p>
<p>将字符在某特定长度下, 句子</p>
<p>StringUtils.center(null, *) = null<br>
StringUtils.center("", 4) = " " <br>
StringUtils.center("ab", -1) = "ab" <br>
StringUtils.center("ab", 4) = " ab " <br>
StringUtils.center("abcd", 2) = "abcd" <br>
StringUtils.center("a", 4) = " a " </p>
<p>public static <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.co
%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title
"class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a> <a href="http
://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-
ang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStr
ngUtils.html%23line.5712" target="_blank" rel="nofollow ugc">capitalize</a>(<a href="https
://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fap
%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang"
arget="_blank" rel="nofollow ugc">String</a> str)</p>
<p>首字母大写</p>
<p>StringUtils.capitalize(null) = null<br>
StringUtils.capitalize("") = "" <br>
StringUtils.capitalize("cat") = "Cat" <br>
StringUtils.capitalize("cAt") = "CAt" </p>
<p>public static <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.co
%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title
"class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a> <a href="http
://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-
ang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStr
ngUtils.html%23line.5795" target="_blank" rel="nofollow ugc">swapCase</a>(<a href="http
://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fap
%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang"
arget="_blank" rel="nofollow ugc">String</a> str)</p>
<p>反向大小写</p>
<p>StringUtils.swapCase(null) = null<br>
StringUtils.swapCase("") = "" <br>
StringUtils.swapCase("The dog has a BONE") = "tHE DOG HAS A bone" </p>
<p>public static boolean <a href="https://ld246.com/forward?goto=http%3A%2F%2Fcomm
ns.apache.org%2Fproper%2Fcommons-lang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg
2Fapache%2Fcommons%2Flang3%2FStringUtils.html%23line.5905" target="_blank" rel="nofo
low ugc">isAlpha</a>(<a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.orac
e.com%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FCharSequence.html%3Fis-external
3Dtrue" title="class or interface in java.lang" target="_blank" rel="nofollow ugc">CharSeque
ce</a> cs)</p>
<p>判断字符串是否由字母组成</p>
<p>StringUtils.isAlpha(null) = false<br>
```

```
StringUtils.isAlpha("") = false<br>
StringUtils.isAlpha(" ") = false<br>
StringUtils.isAlpha("abc") = true<br>
StringUtils.isAlpha("ab2c") = false<br>
StringUtils.isAlpha("ab-c") = false</p>
<p>public static <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.co
%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title
"class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a> <a href="http
://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-
ang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStr
ngUtils.html%23line.6287" target="_blank" rel="nofollow ugc">defaultString</a> (<a href="h
tps://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2
api%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lan
" target="_blank" rel="nofollow ugc">String</a> str,<br>
<a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7
2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface
in java.lang" target="_blank" rel="nofollow ugc">String</a> defaultStr)</p>
<p>默认字符串, 相当于三目运算, 前面弱为空, 则返回后面一个参数</p>
<p>StringUtils.defaultString(null, "NULL") = "NULL" <br>
StringUtils.defaultString("", "NULL") = "" <br>
StringUtils.defaultString("bat", "NULL") = "bat" </p>
<p>public static <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.co
%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title
"class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a> <a href="http
://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-
ang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStr
ngUtils.html%23line.6351" target="_blank" rel="nofollow ugc">reverse</a> (<a href="https://
d246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%
Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang" tar
get="_blank" rel="nofollow ugc">String</a> str)</p>
<p>字符串翻转</p>
<p>StringUtils.reverse(null) = null<br>
StringUtils.reverse("") = "" <br>
StringUtils.reverse("bat") = "tab" </p>
<p>public static <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.co
%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title
"class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a> <a href="http
://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-
ang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStr
ngUtils.html%23line.6421" target="_blank" rel="nofollow ugc">abbreviate</a> (<a href="htt
s://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fap
%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang"
arget="_blank" rel="nofollow ugc">String</a> str,<br>
int maxWidth)</p>
<p>缩略字符串, </p>
<p>省略号要占三位。maxWith 小于 3 位会报错。 </p>
<p>StringUtils.abbreviate(null, *) = null<br>
StringUtils.abbreviate("", 4) = "" <br>
StringUtils.abbreviate("abcdefg", 6) = "abc..." <br>
StringUtils.abbreviate("abcdefg", 7) = "abcdefg" <br>
StringUtils.abbreviate("abcdefg", 8) = "abcdefg" <br>
StringUtils.abbreviate("abcdefg", 4) = "a..." <br>
StringUtils.abbreviate("abcdefg", 3) = IllegalArgumentException</p>
<p>public static <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.co
```

```

%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title
"class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a> <a href="http
://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-
ang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStr
ngUtils.html%23line.6460" target="_blank" rel="nofollow ugc">abbreviate</a>(<a href="htt
s://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fap
%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang"
arget="_blank" rel="nofollow ugc">String</a> str,<br>
int offset,<br>
int maxWidth)</p>
<p>缩略字符串的一些高级用法</p>
<p>StringUtils.abbreviate(null, *, *) = null<br>
StringUtils.abbreviate("", 0, 4) = ""<br>
StringUtils.abbreviate("abcdefghijklmno", -1, 10) = "abcdefg..."<br>
StringUtils.abbreviate("abcdefghijklmno", 0, 10) = "abcdefg..."<br>
StringUtils.abbreviate("abcdefghijklmno", 1, 10) = "abcdefg..."<br>
StringUtils.abbreviate("abcdefghijklmno", 4, 10) = "abcdefg..."<br>
StringUtils.abbreviate("abcdefghijklmno", 5, 10) = "...fghi..."<br>
StringUtils.abbreviate("abcdefghijklmno", 6, 10) = "...ghij..."<br>
StringUtils.abbreviate("abcdefghijklmno", 8, 10) = "...ijklmno"<br>
StringUtils.abbreviate("abcdefghijklmno", 10, 10) = "...ijklmno"<br>
StringUtils.abbreviate("abcdefghijklmno", 12, 10) = "...ijklmno"<br>
StringUtils.abbreviate("abcdefghij", 0, 3) = IllegalArgumentException<br>
StringUtils.abbreviate("abcdefghij", 5, 6) = IllegalArgumentException</p>
<p>public static <a href="https://ld246.com/forward?goto=http%3A%2F%2Fdocs.oracle.co
%2Fjavase%2F7%2Fdocs%2Fapi%2Fjava%2Flang%2FString.html%3Fis-external%3Dtrue" title
"class or interface in java.lang" target="_blank" rel="nofollow ugc">String</a> <a href="http
://ld246.com/forward?goto=http%3A%2F%2Fcommons.apache.org%2Fproper%2Fcommons-
ang%2Fjavadocs%2Fapi-release%2Fsrc-html%2Forg%2Fapache%2Fcommons%2Flang3%2FStr
ngUtils.html%23line.7831" target="_blank" rel="nofollow ugc">wrap</a>(<a href="https://l
246.com/forward?goto=http%3A%2F%2Fdocs.oracle.com%2Fjavase%2F7%2Fdocs%2Fapi%2F
ava%2Flang%2FString.html%3Fis-external%3Dtrue" title="class or interface in java.lang" targe
="_blank" rel="nofollow ugc">String</a> str,<br>
char wrapWith)</p>
<p>包装，用后面的字符串对前面的字符串进行包装</p>
<p>StringUtils.wrap(null, *) = null<br>
StringUtils.wrap("", *) = ""<br>
StringUtils.wrap("ab", '\0') = "ab"<br>
StringUtils.wrap("ab", 'x') = "xabx"<br>
StringUtils.wrap("ab", '') = "'ab'"<br>
StringUtils.wrap("ab", "'") = ""ab""</p>

```