WPF 制作的 wnmp 环境

作者: salamander

- 原文链接: https://ld246.com/article/1522399327533
- 来源网站:链滴
- 许可协议:署名-相同方式共享 4.0 国际 (CC BY-SA 4.0)

WNMP Based On WPF(WPF制作的wnmp环境)

Github

Download(集成包下载)

- 下载地址(Nginx)
- 下载地址(OpenResty)

Main Window(主界面)

Other Functions(其他功能)

Regulaer Settings(常规设置)

Theme Color Panel(调色面板)



Coding Panel(编程面板)

Questions Panel(常见问题面板)

常见问题	×	•
Nginx		٦.
PHP	• 配置root时, 用/, 不要用\	
Composer	 Nginx配置PATHINFO: location ~ \.php { fastcgi_pass 127.0.0.1:9000; fastcgi_index.php; fastcgi_param SCRIPT_FILENAME \$document_root \$fastcgi_param SCRIPT_FILENAME \$document_root \$fastcgi_script_name; fastcgi_split_path_info ^(.+\.php)(.*)\$; fastcgi_param PATH_INFO \$fastcgi_path_info; include fastcgi_params; } \$ 实现URL REWRITE : location / { try_files \$uri \$uri / /index.php\$is_args\$args; } 	

Usage(使用)

下载集成包后,运行SalamanderWnmp.exe(首次运行会自动配置),开启nginx和php,然后在浏 器中输入http://localhost/即可看到Hello Salamander!字样,说明配置成功。(使用数据库功能 则打开mysql)

Notice(注意)

• php 版本为7.1.12 64位版本,需要MSVC14 (Visual C++ 2015)运行库支持,下载: https://do nload.microsoft.com/download/9/3/F/93FCF1E7-E6A4-478B-96E7-D4B285925B00/vc_redist.x 4.exe

• MySQL的默认账户为root, 密码为空

Switch PHP Version(切换PHP版本)

1. 从php官网下载某个版本的PHP, 放入你的wnmp目录中(这里假设下载了PHP5.6, 可以命名为ph 5.6)

2. 修改php.ini (这个文件可以从php.ini-development或php.ini-production重命名过来)中extens on_dir选项,改为wnmp中php5.6的ext目录的绝对路径(举例:D:/SalamanderWnmp/php5.6/ex),另外顺便把一些扩展也加载进来(去掉前面分号即可)

extension=php_bz2.dll extension=php_curl.dll extension=php_fileinfo.dll extension=php_ftp.dll extension=php_gd2.dll extension=php_gettext.dll

- 3. wnmp软件修改php目录配置
- 4. 重启PHP

Third Party Libraries(第三方库)

- AvalonEdit
- StackExchange.Redis

Contact Me(联系我)

- Blog
- segmentfault