

Nginx 配置域名以及映射内网不同端口

作者: [QuinnTian](#)

原文链接: <https://ld246.com/article/1532146473245>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

Nginx.conf

```
upstream tomcat1{
    server 127.0.0.1:8080;
}
upstream tomcat2{
    server 127.0.0.1:8081;
}
server {
    listen 80;
    server_name abc.com;
    location / {

        proxy_pass http://tomcat2;
        proxy_set_header Host $host;
        proxy_set_header X-Real-IP $remote_addr;
        proxy_set_header REMOTE-HOST $remote_addr;
        proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
    }

}

server {
    listen 80;
    server_name abcd.com abcdef.com;
    # root /rest_html/;
    # index index.html;
    #charset koi8-r;

    #access_log logs/host.access.log main;

    location / {
        # root html;
        # index index.html index.htm;
        #域名www.test1.com的请求全部转发到tomcat_server1即tomcat1服务上
        proxy_pass http://tomcat1;
        proxy_set_header Host $host;
        proxy_set_header X-Real-IP $remote_addr;
        proxy_set_header REMOTE-HOST $remote_addr;
        proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
    }
}
```