

Jetty 部署 sym 如何去掉二级目录?

作者: [samye](#)

原文链接: <https://ld246.com/article/1534301472421>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

现在配置的完成后，访问地址是bbs.163.com/sym,如何去掉sym目录，直接输入bbs.163.com就可访问呢？

nginx代理

```
upstream sym {
    server 192.168.1.2:8082;
}

map $http_upgrade $connection_upgrade {
    default upgrade;
    ""      close;
}

server {
    listen      80;
    server_name bbs.163.com;

    location / {

        proxy_pass http://sym$request_uri;
        proxy_http_version 1.1;
        proxy_set_header Host $host:$server_port;
        proxy_set_header X-Real-IP $remote_addr;
        proxy_redirect off;
        proxy_set_header Upgrade $http_upgrade;
        proxy_set_header Connection $connection_upgrade;
    }

}
```

jetty配置

start.ini

```
## Connector host/address to bind to
jetty.http.host=192.168.1.2

## Connector port to listen on
jetty.http.port=8082

# Monitored directory name (relative to $jetty.base)
# jetty.deploy.monitoredDir=webapps
# - OR -
# Monitored directory path (fully qualified)
jetty.deploy.monitoredPath=/www/domain/163.com/webapps
```

latke.properties配置

```
#### Server ####
# Browser visit protocol
serverScheme=http
```

```
# Browser visit domain name
serverHost=bbs.163.com
# Browser visit port, 80 as usual, THIS IS NOT SERVER LISTEN PORT!
serverPort=80
#### Runtime Mode ####
#runtimeMode=DEVELOPMENT
runtimeMode=PRODUCTION
```

解决该问题

在war包目录下面新建一个xml文件，配置下面内容

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE Configure PUBLIC "-//Jetty//Configure//EN" "http://www.eclipse.org/jetty/configure_9_3.dtd">

<Configure class="org.eclipse.jetty.webapp.WebAppContext">
  <Set name="contextPath">/</Set>
  <Set name="war">/www/domain/163.com/webapps/sym.war</Set>
</Configure>
```

参考如下：

<http://www.eclipse.org/jetty/documentation/current/configuring-specific-webapp-deployment.html>