



链滴

# centos7 静态 ip

作者: [someone31950](#)

原文链接: <https://ld246.com/article/1535720403520>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

```
[root@k8s3 ~]# cat /etc/sysconfig/network-scripts/ifcfg-ens33
```

```
TYPE=Ethernet
```

```
PROXY_METHOD=none
```

```
BROWSER_ONLY=no
```

```
BOOTPROTO=static
```

```
DEFROUTE=yes
```

```
IPV4_FAILURE_FATAL=no
```

```
IPV6INIT=yes
```

```
IPV6_AUTOCONF=yes
```

```
IPV6_DEFROUTE=yes
```

```
IPV6_FAILURE_FATAL=no
```

```
IPV6_ADDR_GEN_MODE=stable-privacy
```

```
NAME=ens33
```

```
DEVICE=ens33
```

```
ONBOOT=yes
```

```
IPADDR=192.168.179.139
```

```
GATEWAY=192.168.179.2
```

```
NETMASK=255.255.255.0
```

```
DNS1=114.114.114.114
```

```
DNS2=8.8.8.8
```

```
NM_CONTROLLED=no < =不设置这个networkmanger就会动态另外生成ip
```

然后停止networkmanger并取消随机启动

```
systemctl stop NetworkManager
```

```
systemctl disable NetworkManager
```

重启

```
systemctl restart network.service
```