



链滴

mysql 升级到 5.6

作者: [someone31950](#)

原文链接: <https://ld246.com/article/1535776784611>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

<p>一、导出老版本所有数据</p>

<p>/application/mysql-5.5.48-linux2.6-x86_64/bin/mysqldump -h127.0.0.1 -uroot -pppz2323 -P3306 --all-databases>/root/msyql_backup/mysql5.5_all.sql</p>

<p>wget http://120.52.72.21/ftp.kaist.ac.kr/c3pr90ntc0td/mysql/Downloads/MySQL-5.6/mysql-5.6.36-linux-glibc2.5-x86_64.tar.gz </p>

<p>tar -zxf mysql-5.6.36-linux-glibc2.5-x86_64.tar.gz</p>

<hr>

<p>cp /application/mysql-5.5.48-linux2.6-x86_64/support-files/my-3307.cnf /application/mysql-5.6.36-linux-glibc2.5-x86_64/support-files/</p>

<p>cp /application/mysql-5.5.48-linux2.6-x86_64/support-files/my-3306.cnf /application/mysql-5.6.36-linux-glibc2.5-x86_64/support-files/</p>

<hr>

<p>sed -i 's#mysql-5.5.48-linux2.6-x86_64#mysql-5.6.36-linux-glibc2.5-x86_64#g' my-3306.cnf</p>

<p>sed -i 's#mysql-5.5.48-linux2.6-x86_64#mysql-5.6.36-linux-glibc2.5-x86_64#g' my-3307.cnf</p>

<hr>

<p>mkdir -pv /application/mysql-5.6.36-linux-glibc2.5-x86_64/logs/{3306,3307}</p>

<p>mkdir -pv /application/mysql-5.6.36-linux-glibc2.5-x86_64/data/{3306,3307}</p>

<p>mkdir -pv /application/mysql-5.6.36-linux-glibc2.5-x86_64/socket</p>

<p>mkdir -pv /application/mysql-5.6.36-linux-glibc2.5-x86_64/data/{3306,3307}</p>

<p>mkdir -pv /application/mysql-5.6.36-linux-glibc2.5-x86_64/data/{3306,3307}</p>

<hr>

<p>Chown -R mysql:mysql mysql-5.6.36-linux-glibc2.5-x86_64</p>

<hr>

<p>./mysql_install_db --basedir=/application/mysql-5.6.36-linux-glibc2.5-x86_64 --datadir=/application/mysql-5.6.36-linux-glibc2.5-x86_64/data/3306 --user=mysql</p>

<p>./mysql_install_db --basedir=/application/mysql-5.6.36-linux-glibc2.5-x86_64 --datadir=/application/mysql-5.6.36-linux-glibc2.5-x86_64/data/3307 --user=mysql</p>

<hr>

<p>sed -i 's#mysql-5.5.48-linux2.6-x86_64#mysql-5.6.36-linux-glibc2.5-x86_64#g' /etc/init.d/mysqld1</p>

<p>sed -i 's#mysql-5.5.48-linux2.6-x86_64#mysql-5.6.36-linux-glibc2.5-x86_64#g' /etc/init.d/mysqld2</p>

<hr>

<p>mysql -uroot -pppz2323-----从服务器</p>

<p>mysql> change master to master_host='192.168.179.128',</p>

<p>master_user='mstest',</p>

<p>master_password='123456',</p>

<p>master_log_file='mysql-bin.000001',</p>

<p>master_log_pos=0;</p>

<hr>

<p>start slave;</p>

<p>-----升级后要执行 mysql_upgrade 升级数据结构造成的否则授权时报如下错误</p>

<p>Column count of mysql.user is wrong. Expected 43, found 42. The table is probably corrupted</p>

<p>mysql_upgrade -h ppzCentos1 -uroot -pppz2323 --basedir=/application/mysql-5.6.36-linux-glibc2.5-x86_64/data/3306/ -P3306</p>

<p>mysql_upgrade -h ppzCentos1 -uroot -pppz2323 --basedir=/application/mysql-5.6.36-linux-glibc2.5-x86_64/data/3307/ -P3307</p>