



链滴

# CentOS 装 mysql5.7

作者: [someone26671](#)

原文链接: <https://ld246.com/article/1539074782061>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

## 1. 使用wget下载官方yum源的rpm包

```
wget https://dev.mysql.com/get/mysql57-community-release-el7-11.noarch.rpm
```

## 2. 安装rpm包

```
rpm -ivh mysql57-community-release-el7-11.noarch.rpm
```

## 3. 使用yum来安装mysql-server

```
yum install -y mysql-server
```

## 4. 启动mysql服务

```
systemctl start mysqld
```

## 5. 查看是否启动成功

```
ps aux|grep mysql
```

## 6. 将mysql设置为开机启动

```
systemctl enable mysqld
```

## 7. 查看命令cat 命令查看初始密码 i5j/UEdhcvo% 为初始密码

```
cat /var/log/mysqld.log | grep 'A temporary password'  
2018-10-09T08:09:51.119100Z 1 [Note] A temporary password is generated for root@local  
ost: i5j/UEdhcvo%
```

## 8.使用初始密码登录

```
mysql -uroot -p i5j/UEdhcvo%
```

## 9. 修改数据库密码

```
mysql> ALTER USER 'root'@'localhost' identified by '此处填写新密码';  
Query OK, 0 rows affected (0.00 sec)
```