



链滴

【工具教程】拆分 nginx 配置文件 nginx.conf 的 server, 放到自定义位置

作者: [moonce](#)

原文链接: <https://ld246.com/article/1539614265365>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)



修改后nginx.conf(只要改server内容为 include /etc/nginx/conf.d/*.conf;)

```
#user nobody;
worker_processes 1;

#error_log logs/error.log;
#error_log logs/error.log notice;
#error_log logs/error.log info;

#pid    logs/nginx.pid;

events {
    worker_connections 1024;
}

http {
    include    mime.types;
    default_type application/octet-stream;

    #log_format main '$remote_addr - $remote_user [$time_local] "$request" '
    #                  '$status $body_bytes_sent "$http_referer" '
    #                  '"$http_user_agent" "$http_x_forwarded_for"';

    #access_log logs/access.log main;

    sendfile    on;
    #tcp_nopush  on;
```

```
#keepalive_timeout 0;
keepalive_timeout 65;

#gzip on;
include /etc/nginx/conf.d/*.conf;#加载/etc/nginx/conf.d/路径下所有后缀名为conf的文件,也可以自定义指向其他位置
}
```

在/etc/nginx/conf.d/(include指向的路径)下新建xxx.conf,(xxx一般命名为级域名),可创建多个.

```
server {
    listen     80;
    server_name localhost;

    #charset koi8-r;

    #access_log  logs/host.access.log  main;

    location / {
        root   html;
        index  index.html index.htm;
    }

    error_page 500 502 503 504  /50x.html;
    location = /50x.html {
        root   html;
    }
}
```