



链滴

# ubuntu16 配置静态 ip,hostname

作者: [Smiteli](#)

原文链接: <https://ld246.com/article/1541061233375>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

## 一、配置静态ip:

vim /etc/network/interfaces:

```
iface eth0 inet static
  address 192.168.3.3
  netmask 255.255.255.0
  gateway 192.168.3.1
  dns-search example.com sales.example.com dev.example.com
  dns-nameservers 192.168.3.45 192.168.8.10
```

解释:

If you try to ping a host with the name of server1, your system will automatically query DNS for its Fully Qualified Domain Name (FQDN) in the following order:

1. server1.example.com
2. server1.sales.example.com
3. server1.dev.example.com

If no matches are found, the DNS server will provide a result of notfound and the DNS query will fail.

修改后, 重启网络服务: [/etc/init.d/networking restart](#)

## 二、配置本地hosts文件

vim /etc/hosts:

```
127.0.0.1 localhost
127.0.1.1 ubuntu-server
10.0.0.11 server1 server1.example.com vpn
10.0.0.12 server2 server2.example.com mail
10.0.0.13 server3 server3.example.com www
10.0.0.14 server4 server4.example.com file
```