



链滴

OpenStack (Queens) 搭建之 Dashboard -controller 节点

作者: [limoumou](#)

原文链接: <https://ld246.com/article/1547257417518>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

OpenStack (Queens) 搭建之Dashboard-controller节点

一：安装Dashboard组件

```
yum install openstack-dashboard -y
```

二：编辑 /etc/openstack-dashboard/local_settings

```
OPENSTACK_HOST = "172.30.200.31"
```

```
ALLOWED_HOSTS = ['*']
```

```
SESSION_ENGINE = 'django.contrib.sessions.backends.cache'
```

```
CACHES = {
```

```
    'default': {
```

```
        'BACKEND': 'django.core.cache.backends.memcached.MemcachedCache',
```

```
        'LOCATION': '172.16.14.224:11211',
```

```
    }  
}
```

```
OPENSTACK_KEYSTONE_URL = "http://%s:5000/v3" % OPENSTACK_HOST
```

```
OPENSTACK_KEYSTONE_MULTIDOMAIN_SUPPORT = True
```

```
OPENSTACK_KEYSTONE_DEFAULT_ROLE = "user"
```

```
OPENSTACK_API_VERSIONS = {
```

```
    "identity": 3,
```

```
    "image": 2,
```

```
    "volume": 2,
```

```
}
```

```
OPENSTACK_KEYSTONE_DEFAULT_DOMAIN = "Default"
```

```
OPENSTACK_NEUTRON_NETWORK = {
```

```
    'enable_router': False,
```

```
    'enable_quotas': False,
```

```
    'enable_distributed_router': False,
```

```
    'enable_ha_router': False,
```

```
    'enable_lb': False,
```

```
    'enable_firewall': False,
```

```
    'enable_vpn': False,
```

```
    'enable_fip_topology_check': False,
```

```
}
```

```
TIME_ZONE = "Asia/Shanghai"
```

三：重启HTTP和Memcached服务

```
systemctl restart httpd memcached
```

四：验证登陆

在浏览器输入 <https://1d246.com/forward?goto=http%3A%2F%2F172.30.200.31%>

`Fdashboard" class="url" target="_blank" rel="nofollow ugc">http://172.30.200.31/dashboar`
`.,访问openstack的web页面</p>`