



链滴

查看 centos7 上是否安装了 mariadb

作者: [branda2019wj](#)

原文链接: <https://ld246.com/article/1554364984425>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

废话不多说，进入正题。

1 打开虚拟机，输入命令，查看是否安装了mariadb

命令：rpm -qa | grep mariadb # 查看是否安装了mariadb

rpm的用法：rpm --help

```
[root@localhost ~]# rpm --help
Usage: rpm [OPTION...]

Query/Verify package selection options:
-a, --all                query/verify all packages
-f, --file                query/verify package(s) owning file
-g, --group               query/verify package(s) in group
-p, --package            query/verify a package file
--pkgid                  query/verify package(s) with package identifier
--hdrid                  query/verify package(s) with header identifier
--triggeredby            query the package(s) triggered by the package
--whatrequires            query/verify the package(s) which require a dependency
--whatprovides            query/verify the package(s) which provide a dependency
--nomanifest              do not process non-package files as manifests
```

运行结果：下图表明安装了mariadb

```
[root@localhost ~]# rpm -qa | grep mariadb
mariadb-embedded-devel-5.5.56-2.el7.x86_64
mariadb-embedded-5.5.56-2.el7.x86_64
mariadb-devel-5.5.56-2.el7.x86_64
mariadb-test-5.5.56-2.el7.x86_64
mariadb-5.5.56-2.el7.x86_64
mariadb-server-5.5.56-2.el7.x86_64
mariadb-bench-5.5.56-2.el7.x86_64
mariadb-libs-5.5.56-2.el7.x86_64
```

2 查看mariadb安装的状态：service mariadb status

```
[root@localhost ~]# service mariadb status
Redirecting to /bin/systemctl status mariadb.service
● mariadb.service - MariaDB database server
   Loaded: loaded (/usr/lib/systemd/system/mariadb.service; disabled; vendor preset: disabled)
   Active: inactive (dead)
```

上图的状态表明mariadb没有启动

3 启动mariadb，输入命令：service mariadb start

```
[root@localhost ~]# service mariadb start
Redirecting to /bin/systemctl start mariadb.service
```

4 再次查看mariadb状态

```
[root@localhost ~]# service mariadb status
Redirecting to /bin/systemctl status mariadb.service
● mariadb.service - MariaDB database server
   Loaded: loaded (/usr/lib/systemd/system/mariadb.service; disabled; vendor preset: disabled)
   Active: active (running) since Thu 2019-04-04 03:37:15 EDT; 19min ago
     Process: 4627 ExecStartPost=/usr/libexec/mariadb-wait-ready $MAINPID (code=exited, status=0/SUCCESS)
     Process: 4596 ExecStartPre=/usr/libexec/mariadb-prepare-db-dir %n (code=exited, status=0/SUCCESS)
    Main PID: 4626 (mysqld_safe)
      CGroup: /system.slice/mariadb.service
              └─4626 /bin/sh /usr/bin/mysqld_safe --basedir=/usr
                 └─4789 /usr/libexec/mysqld --basedir=/usr --datadir=/var/lib/mysql --plugin-dir=/usr/lib/mysql/plugin

Apr 04 03:37:12 localhost.localdomain systemd[1]: Starting MariaDB database server...
Apr 04 03:37:12 localhost.localdomain mariadb-prepare-db-dir[4596]: Database MariaDB is pr
Apr 04 03:37:13 localhost.localdomain mysqld_safe[4626]: 190404 03:37:13 mysqld_safe Logg
Apr 04 03:37:13 localhost.localdomain mysqld_safe[4626]: 190404 03:37:13 mysqld_safe Star
Apr 04 03:37:15 localhost.localdomain systemd[1]: Started MariaDB database server.
Hint: Some lines were ellipsized, use -l to show in full.
```

如果出现上图标红的标志，说明成功启动

原创申明：以上内容来自于个人经验，如需转载，请注明出处