



链滴

Mybatis Auto Generate

作者: [liumeijian](#)

原文链接: <https://ld246.com/article/1557845107702>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

pom.xml

```
<!--mybatis代码自动生成插件-->
<plugin>
  <groupId>org.mybatis.generator</groupId>
  <artifactId>mybatis-generator-maven-plugin</artifactId>
  <version>1.3.7</version>
  <dependencies>
    <dependency>
      <groupId>mysql</groupId>
      <artifactId>mysql-connector-java</artifactId>
      <version>5.1.27</version>
    </dependency>
    <dependency>
      <groupId>org.mybatis.generator</groupId>
      <artifactId>mybatis-generator-core</artifactId>
      <version>1.3.7</version>
    </dependency>
  </dependencies>
  <configuration>
    <!--允许移动生成的文件 -->
    <verbose>true</verbose>
    <!-- 是否覆盖 -->
    <overwrite>false</overwrite>
    <!-- 自动生成的配置 -->
    <configurationFile>
      src/main/resources/mybatis-generator-mysql.xml</configurationFile>
    </configuration>
  </plugin>
```

mybatis-generator-mysql.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE generatorConfiguration
  PUBLIC "-//mybatis.org//DTD MyBatis Generator Configuration 1.0//EN"
  "http://mybatis.org/dtd/mybatis-generator-config_1_0.dtd">
<generatorConfiguration>
  <context id="DB2Tables" targetRuntime="MyBatis3">
    <commentGenerator>
      <property name="suppressDate" value="true"/>
      <property name="suppressAllComments" value="fale"/>
      <property name="addRemarkComments" value="true"/>
      <property name="author" value="zhaozb"/>
    </commentGenerator>
    <!--数据库链接地址账号密码,配置开发环境连接-->
    <jdbcConnection driverClass="com.mysql.jdbc.Driver"
      B8" connectionURL="jdbc:mysql://localhost:3306/test_db?serverTimezone=GMT%
      userId="uesrname"
      password="password" >
    </jdbcConnection>
    <javaTypeResolver>
```

```

    <property name="forceBigDecimals" value="false"/>
</javaTypeResolver>

<!--生成Model类存放位置-->
<javaModelGenerator targetPackage="com.liumj.model" targetProject="src/main/java">
    <property name="enableSubPackages" value="true"/>
    <property name="trimStrings" value="true"/>
</javaModelGenerator>

<!--生成映射文件存放位置-->
<sqlMapGenerator targetPackage="com.liumj.dbMapper.mysql" targetProject="src/main/java">
    <property name="enableSubPackages" value="true"/>
</sqlMapGenerator>
<!--生成Dao类存放位置-->
<!-- 客户端代码，生成易于使用的针对Model对象和XML配置文件的代码
    type="ANNOTATEDMAPPER",生成Java Model 和基于注解的Mapper对象
    type="MIXEDMAPPER",生成基于注解的Java Model 和相应的Mapper对象
    type="XMLMAPPER",生成SQLMap XML文件和独立的Mapper接口
-->
<javaClientGenerator type="XMLMAPPER" targetPackage="com.liumj.dao" targetProject="src/main/java">
    <property name="enableSubPackages" value="true"/>
</javaClientGenerator>

<!--生成对应表及类名-->
<!--
    <table tableName="test_table" domainObjectName="Test" mapperName="TestDao"
enableCountByExample="false" enableUpdateByExample="false" enableDeleteByExample="false"
enableSelectByExample="false" selectByExampleQueryId="false" />
-->
</context>
</generatorConfiguration>

```