



链滴

solo 在 centos 上使用 tomcat 部署遇到的配置报错问题?

作者: [abelkeith](#)

原文链接: <https://ld246.com/article/1559131841818>

来源网站: 链滴

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

以下是相关配置

latke 配置

```
#### Server ####  
  
# Browser visit protocol  
serverScheme=http  
#serverHost=localhost  
#serverPort=  
  
#### Runtime Mode ####  
#runtimeMode=DEVELOPMENT  
runtimeMode=PRODUCTION  
  
# Browser visit domain name  
serverHost=172.18.230.18  
# Browser visit port,80 as usual. this is not server listen port  
serverPort=8080  
~
```

local 配置

```
#### MySQL runtime ####  
#runtimeDatabase=MYSQL  
#jdbc.username=root  
#jdbc.password=123456  
#jdbc.driver=com.mysql.cj.jdbc.Driver  
#jdbc.URL=jdbc:mysql://localhost:3306/solo?useUnicode=yes&characterEncoding=UTF-8&u  
eSSL=false&serverTimezone=UTC  
  
#### H2 runtime ####  
runtimeDatabase=H2  
jdbc.username=root  
jdbc.password=  
jdbc.driver=org.h2.Driver  
jdbc.URL=jdbc:h2:~/solo_h2/db;MODE=MYSQL  
  
# The minConnCnt MUST larger or equal to 3  
jdbc.minConnCnt=5  
jdbc.maxConnCnt=10  
  
# The specific table name prefix  
jdbc.tablePrefix=b3_solo
```