



链滴

# cas5.3.x 配置返回多属性问题 (java 客户端无法获取服务器返回的自定义信息)

作者: [kkk](#)

原文链接: <https://ld246.com/article/1567569219812>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

## 问题如题：

其中参照了

<https://www.jianshu.com/p/54646ac96473>

<https://blog.csdn.net/yellowcong/article/details/79238335>

并根据教程做了如下配置：

1、修改service文件，HTTPS and IMAPS-10000001.json

```
{
  "@class" : "org.apereo.cas.services.RegexRegisteredService",
  "serviceId" : "^(http|https|imaps)://.*",
  "name" : "HTTPS and IMAPS",
  "id" : 10000001,
  "description" : "This service definition authorizes all application urls that support HTTPS and
MAPS protocols.",
  "evaluationOrder" : 10000,
  "attributeReleasePolicy" : {
    "@class" : "org.apereo.cas.services.ReturnAllAttributeReleasePolicy"
  }
}
```

2、自定义验证以及返回更多的个人信息

3、spring.factories文件配上自己自定义的流程，其他的去掉

```
org.springframework.boot.autoconfigure.EnableAutoConfiguration=com.gxzytech.config.Cus
omAuthenticationConfiguration
```

4、查看后台服务器，确实返回了新加的信息

```
logger.info("校验成功");
//可自定义返回给客户端的多个属性信息
HashMap<String, Object> returnInfo = new HashMap<>(); returnInfo: size = 3
returnInfo.put(k: "username", info.getUsername());
returnInfo.put(k: "mobil_no", info.getTel());
returnInfo.put(k: "email", info.getEmail()); info: User@12921
final List<MessageDescriptor> list = new ArrayList<>(); list: size = 0
return createHandlerResult(credential, this.principalFactory.createPrincipal(username, returnInfo), list);
} else {
    throw new FailedLoginException("密码错误!");
}
}

CustomUsernamePasswordAuthenticationHandler.authenticateUsernamePasswordInternal()

Variables
2,402 in group "main": RUNNING
password = "hg123456"
sql = "select byname as username, mobil_no as tel, email, password FROM use
info = {User@12921}
pass = "${od1.dZ4.$JG3JFnVxR/Gri/PKdUC7k1}"
returnInfo = {HashMap@12935} size = 3
0 = {HashMap$Node@12941} "mobil_no" -> "12345678111"
1 = {HashMap$Node@12942} "email" -> "123456@126"
2 = {HashMap$Node@12943} "username" -> "admin"
```

## 最后问题是，java客户端还是只返回了用户名

### CAS Example Java Web App

A sample web application that exercises the CAS protocol features via the Java CAS Client.

Authenticated User Id: [admin](#)

Attributes:

Attributes	
Key	Value
credentialType	UsernamePasswordCredential
isFromNewLogin	true
authenticationDate	2019-09-04T11:28:50.222+08:00[Asia/Shanghai]
authenticationMethod	com.garyt.duke.config.CustomUsernamePasswordAuthentication
successfulAuthenticationHandlers	com.garyt.duke.config.CustomUsernamePasswordAuthentication
longTermAuthenticationRequestTokenUsed	false

求助客户端如何才能获得自定义的信息?