



链滴

SpringBoot 读取配置文件

作者: [Joshxubo](#)

原文链接: <https://ld246.com/article/1570616669600>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)



SpringBoot读取配置文件

1.IO流读取机密文件(打jar可读取)

```
InputStream inputStream = AuthorizationHelper.class.getClassLoader()  
    .getResourceAsStream("META-INF/default-public.pem");
```

```
StringBuilder builder = new StringBuilder();  
Assert.notNull(inputStream,()->"inputStream is null");  
BufferedInputStream bis = new BufferedInputStream(inputStream,1024);  
byte[] buffer = new byte[1024];  
int length = 0;  
while ((length = bis.read(buffer))!=-1){  
    builder.append(new String(buffer,0,length, StandardCharsets.UTF_8));  
}  
String publicKeyStr = builder.toString();
```

2.@EnableConfigurationProperties 读取配置文件

```
@Configuration  
@EnableConfigurationProperties({RemoteServerProperties.class})  
public class RemoteConfiguration {  
    //properties配置文件前缀  
    @ConfigurationProperties(prefix = "remote.url")  
    @Data  
    public static class RemoteServerProperties{  
        //aorpApiServer 对应properties文件的aorp-api-server  
        private String aorpApiServer;  
    }  
}
```

//properties配置文件

remote.url.aorp-api-server: http://192.168.1.159:7777/aorp

3.@Value读取配置文件(维护成本高)