链滴

启动、停止 MySQL 服务和 MySQL 常用参数

如何启动MySQL服务

以管理员身份运行cmd

然后输入命令 net start MySQL的服务名，启动服务，因为我的电脑里MySQL服务名为MySQL57，
以输入net start MySQL57

如何停止MySQL服务

同意如上，以管理员身份运行cmd，输入net stop MySQL的服务名，停止服务，我的电脑里MySQL
务名为MySQL57，所以输入net start MySQL57

如何登陆MySQL

启动服务后，再cmd里输入mysql -u root -p -P 306 -h 127.0.0.1，这里-u是用户名，-p是密码，-P端口号，如果你是默认的端口3306未修改过，可以省略-P参数，如果是连接的本地服务器，-h参数可以不加

```
C:\WINDOWS\system32>mysql -u root -p -P 3306 -h 127.0.0.1
Enter password:
```

然后它会提示输入密码，输入密码后登陆成功

```
C:\WINDOWS\system32>mysql -u root -p -P 3306 -h 127.0.0.1
Enter password: *********
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 3
Server version: 5.7.28-log MySQL Community Server (GPL)

Copyright (c) 2000, 2019, Oracle and/or its affiliates. All rights reserved.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql>
```

常用参数：

-u——用户名
-p——密码
-h——服务器名称
-P——端口号
-v——版本号
--prompt——提示符

如何退出MySQL

第一种：mysql > exit;

输入exit; 退出mysql

```
C:\WINDOWS\system32>mysql -u root -p
Enter password: *********
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 9
Server version: 5.7.28-log MySQL Community Server (GPL)

Copyright (c) 2000, 2019, Oracle and/or its affiliates. All rights reserved.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> exit;
Bye

C:\WINDOWS\system32>
```

第二种：mysql > quit;

输入quit; 退出mysql

原文链接：启动、停止 MySQL 服务和 MySQL 常用参数

第三种：mysql > \q;

输入\q; 退出mysql

修改MySQL提示符

连接客户端时通过参数指定：mysql -u root -p --prompt abc

连接客户端后，通过prompt命令修改：mysql>prompt abc