



链滴

Nginx 的 Https 配置

作者: [henryspace](#)

原文链接: <https://ld246.com/article/1591880625855>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

一，准备工作

- 证书密钥，推荐 [Freessl](#)
- Nginx服务器

二，修改配置文件

1, ssl配置文件ssl.conf

```
server {
    listen    443 ssl;
    server_name yourdomain.com;

    # 项目路径
    root     /www/trunk;

    # 配证书的pem|key文件地址
    ssl_certificate /etc/cert/yoursignature.pem;
    ssl_certificate_key /etc/cert/yoursignature.key;

    ssl_session_cache shared:SSL:1m;
    ssl_session_timeout 10m;
    ssl_ciphers ssl_ciphers ECDHE-RSA-AES128-GCM-SHA256:ECDHE:ECDH:AES:HIGH:!NULL:!a
ULL:!MD5:!ADH:!RC4;
    ssl_protocols TLSv1 TLSv1.1 TLSv1.2;
    ssl_prefer_server_ciphers on;

    # Load configuration files for the default server block.
    # include /etc/nginx/default.d/*.conf;

    location / {
        root /www/trunk;
        index index.php index.html index.htm;
    }

    error_page 404 /404.html;
    location = /404.html {
        root /usr/share/nginx/html;
    }

    error_page 500 502 503 504 /50x.html;
    location = /50x.html {
        root /usr/share/nginx/html;
    }

    # pass the PHP scripts to FastCGI server listening on 127.0.0.1:9000
    #
    location ~ \.php$ {
        root /www/trunk;
        fastcgi_pass 127.0.0.1:9000;
        fastcgi_index index.php;
        fastcgi_param SCRIPT_FILENAME /www/trunk$fastcgi_script_name;
    }
}
```

```
    include    fastcgi_params;
}

# deny access to .htaccess files, if Apache's document root
# concurs with nginx's one
#
location ~ /\.ht {
    deny all;
}
}
```

2, 修改nginx默认配置default.conf

```
server {
    listen 80;
    server_name yourdomain.com;

    rewrite ^(.*)$ https://$host$1 permanent;
}
```

三, 重启Nginx

```
systemctl restart nginx.service
```