链滴

Haproxy 配置

作者：cuijianzhe

Haproxy

haproxy配置文件

```
[root@ali-pro-ops-ldap_blance ~]# cat /usr/local/haproxy/conf/haproxy.cfg
global
    log 127.0.0.1 local3
    log 127.0.0.1 local1 notice
    stats timeout 30s
        uid 99
        gid 99
        daemon
#       nbproc 4
#       chroot /usr/local/haproxy
        pidfile /usr/local/haproxy/run/haproxy.pid
        chroot /usr/local/haproxy
defaults
    log global
    mode http
    option httplog
    option dontlognull
    timeout connect 5000
    timeout client  50000
    timeout server  50000

listen LDAP-10389
    bind 0.0.0.0:10389
    mode tcp
        option tcplog
    maxconn 2000
    timeout connect 5000
    timeout client  50000
    timeout server  50000
#    balance roundrobin
        balance leastconn
    server LDAP1             172.16.16.4:389                        check inter 30000 fastinter
000
    server LDAP2_Via_SocksProxy1 172.16.16.35:389                       check inter 30000
astinter 1000

# HAProxy web ui
listen stats
    bind 0.0.0.0:20000
    mode http
    log global

    maxconn 10
    timeout client 100s
    timeout server 100s
    timeout connect 100s
    timeout queue 100s
```

```
stats enable
stats uri /haproxy?stats
stats realm HAProxy\ Statistics
stats admin if TRUE
stats show-node
```


HAProxy version 2.3-dev1, released 2020/07/17

Statistics Report for pid 18794 on all-pro-ops-ldap_blance

参考：

1. https://www.cnblogs.com/happy1983/p/9265358.html

2. http://cbonte.github.io/haproxy-dconv/2.3/configuration.html#balance

3. https://www.cnblogs.com/nmap/p/8781296.html