



链滴

centos 软件安装 -rabbitmq

作者: [xuyan1095](#)

原文链接: <https://ld246.com/article/1605167444638>

来源网站: [链滴](#)

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

<p>1.安装依赖</p>

```
<script async src="https://pagead2.googlesyndication.com/pagead/js/adsbygoogle.js?client=a-pub-5357405790190342" crossorigin="anonymous"></script> <!-- 黑客派PC帖子内嵌 -->
<ins class="adsbygoogle" style="display:block" data-ad-client="ca-pub-5357405790190342" data-ad-slot="8316640078" data-ad-format="auto" data-full-width-responsive="true"></in
>
```

```
<script>
```

```
  (adsbygoogle = window.adsbygoogle || []).push({};
```

```
</script>
```

```
<p>rpm -ivh --force erlang-22.3.4.2-1.el7.x86_64.rpm</p>
```

```
<p>rpm -ivh --force socat-1.7.3.2-2.el7.x86_64.rpm</p>
```

```
<p>rpm -ivh --force logrotate-3.8.6-19.el7.x86_64.rpm</p>
```

<p>2.安装</p>

```
<p>rpm -ivh --force rabbitmq-server-3.8.5-1.el7.noarch.rpm</p>
```

<p>3.测试是否安装成功: </p>

<p>【开启 rabbitmq 服务】 </p>

```
<p>chkconfig rabbitmq-server on</p>
```

<p>【查看服务状态: 】 </p>

```
<p>systemctl status rabbitmq-server</p>
```

<p>【开启 rabbitmq: 】 </p>

```
<p>systemctl start rabbitmq-server</p>
```

<p>【开启管理插件: 】 </p>

```
<p>rabbitmq-plugins enable rabbitmq_management</p>
```

<p>【查看插件集合: 】 </p>

```
<p>rabbitmq-plugins list</p>
```

<p>4.用户管理</p>

<p>#查看所有用户</p>

```
<p>rabbitmqctl list_users</p>
```

<p>#添加一个用户</p>

```
<p>rabbitmqctl add_user admin 123456</p>
```

<p>#配置权限</p>

```
<p>rabbitmqctl set_permissions -p "/" admin ".<em>" ".</em>" ".*"</p>
```

<p>#查看用户权限</p>

```
<p>rabbitmqctl list_user_permissions admin</p>
```

<p>#设置 tag</p>

```
<p>rabbitmqctl set_user_tags admin administrator</p>
```

<p>#删除用户 (安全起见, 删除默认用户) </p>

```
<p>rabbitmqctl delete_user guest</p>
```