



链滴

solo 启动 docker 报错

作者: [max125ytj](#)

原文链接: <https://ld246.com/article/1609210896413>

来源网站: 链滴

许可协议: [署名-相同方式共享 4.0 国际 \(CC BY-SA 4.0\)](#)

```
<p>配置</p>
<script async src="https://pagead2.googlesyndication.com/pagead/js/adsbygoogle.js"></scr
pt>
<!-- 黑客派PC帖子内嵌-展示 -->
<ins class="adsbygoogle" style="display:block" data-ad-client="ca-pub-5357405790190342"
data-ad-slot="8316640078" data-ad-format="auto" data-full-width-responsive="true"></in
>
<script>
  (adsbygoogle = window.adsbygoogle || []).push({});
</script>
<pre><code class="highlight-chroma">version: "2"
```

services:

mysql:

container_name: solo-mysql

image: mysql:5.7.13

restart: always

volumes:

- /opt/docker/solo/mysql/data:/var/lib/mysql
- /opt/docker/solo/mysql/logs:/logs
- /opt/docker/solo/mysql/conf:/etc/mysql/conf.d
- /etc/localtime:/etc/localtime:ro

ports:

- "3306:3306"

environment:

MYSQL_ROOT_PASSWORD: 123456

TZ: "Asia/Shanghai"

command: --max_allowed_packet=32505856

solo:

container_name: solo

image: b3log/solo:latest

restart: always

ports:

- "8080:8080"

environment:

RUNTIME_DB: "MYSQL"

JDBC_USERNAME: "root"

JDBC_PASSWORD: "123456"

JDBC_DRIVER: "com.mysql.cj.jdbc.Driver"

JDBC_URL: "jdbc:mysql://127.0.0.1:3306/solo?useUnicode=yes&";

```
characterEncoding=UTF-8&useSSL=false
&serverTimezone=UTC&allowPublicKeyRetrieval=true"
```

```
command: --listen_port=8080 --server_scheme=http --server_host=localhost --server_port=
nginx:
```

```
container_name: solo-nginx
```

```
image: nginx:latest
```

```
restart: always
```

```
ports:
```

```
- "80:80"
```

```
- "443:443"
```

```
volumes:
```

```
- /opt/docker/nginx/conf/nginx.conf:/etc/nginx/nginx.conf
```

```
- /opt/docker/nginx/conf/conf.d:/etc/nginx/conf.d
```

```
- /opt/docker/nginx/html:/usr/share/nginx/html
```

```
- /opt/docker/nginx/logs:/var/log/nginx
```

```
</code></pre>
```

<p>报错</p>

```
<pre><code class="highlight-chroma">solo exited with code 255
```

```
solo | [INFO ]-[2020-12-29 10:58:42]-[org.b3log.solo.Server:253]: Solo is booting [ver=4.3.1,
os=Linux, isDocker=true, inJar=false, luteAvailable=false, pid=1, runtimeDatabase=MYSQL, r
untimeMode=PRODUCTION, jdbc.username=root, jdbc.URL=jdbc:mysql://localhost:3306/solo
useUnicode=yes&characterEncoding=UTF-8&useSSL=false&serverTimezone
UTC&allowPublicKeyRetrieval=true]
```

```
solo | [ERROR]-[2020-12-29 10:58:45]-[com.zaxxer.hikari.pool.HikariPool:593]: HikariPool-1 -
Exception during pool initialization.
```

```
solo | com.mysql.cj.jdbc.exceptions.CommunicationsException: Communications link failure
```

```
solo |
```

```
solo | The last packet sent successfully to the server was 0 milliseconds ago. The driver has
ot received any packets from the server.
```

```
solo | at com.mysql.cj.jdbc.exceptions.SQLException.createCommunicationsException(SQLExcep
tion.java:174) ~[mysql-connector-java-8.0.20.jar:8.0.20]
```

```
solo | at com.mysql.cj.jdbc.exceptions.SQLExceptionsMapping.translateException(SQLExcep
tionsMapping.java:64) ~[mysql-connector-java-8.0.20.jar:8.0.20]
```

```
solo | at com.mysql.cj.jdbc.ConnectionImpl.createNewIO(ConnectionImpl.java:836) ~[mysq
l-connector-java-8.0.20.jar:8.0.20]
```

```
solo | at com.mysql.cj.jdbc.ConnectionImpl.&lt;init&gt;(ConnectionImpl.java:456) ~[mysq
l-connector-java-8.0.20.jar:8.0.20]
```

```
solo | at com.mysql.cj.jdbc.ConnectionImpl.getInstance(ConnectionImpl.java:246) ~[mysq
l-connector-java-8.0.20.jar:8.0.20]
```

```
solo | at com.mysql.cj.jdbc.NonRegisteringDriver.connect(NonRegisteringDriver.java:197)
~[mysql-connector-java-8.0.20.jar:8.0.20]
```

```
solo | at com.zaxxer.hikari.util.DriverDataSource.getConnection(DriverDataSource.java:13
) ~[HikariCP-3.4.5.jar:?]
```

```
solo | at com.zaxxer.hikari.pool.PoolBase.newConnection(PoolBase.java:358) ~[HikariCP-3
.4.5.jar:?]
```

```
solo | at com.zaxxer.hikari.pool.PoolBase.newPoolEntry(PoolBase.java:206) ~[HikariCP-3.4
.5.jar:?]
```

```

solo | at com.zaxxer.hikari.pool.HikariPool.createPoolEntry(HikariPool.java:477) [HikariCP
3.4.5.jar:?]
solo | at com.zaxxer.hikari.pool.HikariPool.checkFailFast(HikariPool.java:560) [HikariCP-3.4
5.jar:?]
solo | at com.zaxxer.hikari.pool.HikariPool.&lt;init&gt;(HikariPool.java:115) [HikariCP-3.4.5
jar:?]
solo | at com.zaxxer.hikari.HikariDataSource.getConnection(HikariDataSource.java:112) [H
ikariCP-3.4.5.jar:?]
solo | at org.b3log.latke.repository.jdbc.util.Connections.getConnection(Connections.java
196) [latke-core-3.4.10.jar:?]
solo | at org.b3log.solo.service.InitService.initTables(InitService.java:165) [solo/:?]
solo | at org.b3log.solo.service.InitService_$$jvst5a4_47._d7initTables(InitService_$$jvst
a4_47.java) [solo/:?]
solo | at sun.reflect.NativeMethodAccessorImpl.invoke0(Native Method) ~[?:1.8.0_212]
solo | at sun.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:
2) ~[?:1.8.0_212]
solo | at sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorI
pl.java:43) ~[?:1.8.0_212]
solo | at java.lang.reflect.Method.invoke(Method.java:498) ~[?:1.8.0_212]
solo | at org.b3log.latke.ioc.JavassistMethodHandler.invoke(JavassistMethodHandler.java
108) [latke-core-3.4.10.jar:?]
solo | at org.b3log.solo.service.InitService_$$jvst5a4_47.initTables(InitService_$$jvst5a4
47.java) [solo/:?]
solo | at org.b3log.solo.Server.main(Server.java:266) [solo/:?]
solo | Caused by: com.mysql.cj.exceptions.CJCommunicationsException: Communications li
k failure
solo |
solo | The last packet sent successfully to the server was 0 milliseconds ago. The driver has
ot received any packets from the server.
solo | at sun.reflect.NativeConstructorAccessorImpl.newInstance0(Native Method) ~[?:1.8
0_212]
solo | at sun.reflect.NativeConstructorAccessorImpl.newInstance(NativeConstructorAcces
orImpl.java:62) ~[?:1.8.0_212]
solo | at sun.reflect.DelegatingConstructorAccessorImpl.newInstance(DelegatingConstruc
torAccessorImpl.java:45) ~[?:1.8.0_212]
solo | at java.lang.reflect.Constructor.newInstance(Constructor.java:423) ~[?:1.8.0_212]
solo | at com.mysql.cj.exceptions.ExceptionFactory.createException(ExceptionFactory.java
61) ~[mysql-connector-java-8.0.20.jar:8.0.20]
solo | at com.mysql.cj.exceptions.ExceptionFactory.createException(ExceptionFactory.java
105) ~[mysql-connector-java-8.0.20.jar:8.0.20]
solo | at com.mysql.cj.exceptions.ExceptionFactory.createException(ExceptionFactory.java
151) ~[mysql-connector-java-8.0.20.jar:8.0.20]
solo | at com.mysql.cj.exceptions.ExceptionFactory.createCommunicationsException(Exce
tionFactory.java:167) ~[mysql-connector-java-8.0.20.jar:8.0.20]
solo | at com.mysql.cj.protocol.a.NativeSocketConnection.connect(NativeSocketConnecti
n.java:91) ~[mysql-connector-java-8.0.20.jar:8.0.20]
solo | at com.mysql.cj.NativeSession.connect(NativeSession.java:144) ~[mysql-connector-
ava-8.0.20.jar:8.0.20]
solo | at com.mysql.cj.jdbc.ConnectionImpl.connectOneTryOnly(ConnectionImpl.java:956)
~[mysql-connector-java-8.0.20.jar:8.0.20]
solo | at com.mysql.cj.jdbc.ConnectionImpl.createNewIO(ConnectionImpl.java:826) ~[my
ql-connector-java-8.0.20.jar:8.0.20]
solo | ... 20 more
solo | Caused by: java.net.NoRouteToHostException: Host is unreachable (Host unreachable

```

```
solo | at java.net.PlainSocketImpl.socketConnect(Native Method) ~[?:1.8.0_212]
solo | at java.net.AbstractPlainSocketImpl.doConnect(AbstractPlainSocketImpl.java:350) ~
?:1.8.0_212]
solo | at java.net.AbstractPlainSocketImpl.connectToAddress(AbstractPlainSocketImpl.jav
:206) ~[?:1.8.0_212]
solo | at java.net.AbstractPlainSocketImpl.connect(AbstractPlainSocketImpl.java:188) ~[?:
.8.0_212]
solo | at java.net.SocksSocketImpl.connect(SocksSocketImpl.java:392) ~[?:1.8.0_212]
solo | at java.net.Socket.connect(Socket.java:589) ~[?:1.8.0_212]
solo | at com.mysql.cj.protocol.StandardSocketFactory.connect(StandardSocketFactory.ja
a:155) ~[mysql-connector-java-8.0.20.jar:8.0.20]
solo | at com.mysql.cj.protocol.a.NativeSocketConnection.connect(NativeSocketConnecti
n.java:65) ~[mysql-connector-java-8.0.20.jar:8.0.20]
solo | at com.mysql.cj.NativeSession.connect(NativeSession.java:144) ~[mysql-connector-
ava-8.0.20.jar:8.0.20]
solo | at com.mysql.cj.jdbc.ConnectionImpl.connectOneTryOnly(ConnectionImpl.java:956)
~[mysql-connector-java-8.0.20.jar:8.0.20]
solo | at com.mysql.cj.jdbc.ConnectionImpl.createNewIO(ConnectionImpl.java:826) ~[my
ql-connector-java-8.0.20.jar:8.0.20]
solo | ... 20 more
solo | [ERROR]-[2020-12-29 10:58:45]-[org.b3log.solo.service.InitService:173]: Check tables
ailed, please make sure database existed and database configuration [jdbc.*] in local.props is
orrect [msg=Communications link failure
solo |
solo | The last packet sent successfully to the server was 0 milliseconds ago. The driver has
ot received any packets from the server.]
^CGracefully stopping... (press Ctrl+C again to force)
```

</code></pre>

```
<script async src="https://pagead2.googlesyndication.com/pagead/js/adsbygoogle.js"></scr
ipt>
```

```
<!-- 黑客派PC帖子内嵌-展示 -->
```

```
<ins class="adsbygoogle" style="display:block" data-ad-client="ca-pub-5357405790190342"
data-ad-slot="8316640078" data-ad-format="auto" data-full-width-responsive="true"></in
>
<script>
  (adsbygoogle = window.adsbygoogle || []).push({});
</script>
<p>有人知道 怎么改, 什么问题吗? </p>
```